



DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Date of issue: 14-11-2006

Revision date: 9-4-2018

Supersedes: 31-5-2017

Version: 6.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : DRY FLEX® 4 - Component B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
Use of the substance/mixture : Elastic repair compound
Product only to be used in combination with component A.

1.2.2. Uses advised against

No additional information available.

1.3. Details of the supplier of the safety data sheet

Repair Care International
Cartografenweg 34
5141 MT Waalwijk - Nederland
T + 31(0) 416 650095 - F + 31(0) 416 652024
info@repair-care.com - www.repair-care.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Remark
United Kingdom	National Poisons Information Service (Belfast Centre) Royal Victoria Hospital	Grosvenor Road BT12 6BA Belfast	0344 892 0111	Only for the purpose of informing medical personnel in cases of acute intoxications

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179

Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 1B H314
Skin sensitisation, Category 1 H317
Reproductive toxicity, Category 2 H361
Specific target organ toxicity — Repeated exposure, Category 1 H372
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes severe skin burns and eye damage. Toxic to aquatic life with long lasting effects. May cause harm to breast-fed children. May damage fertility or the unborn child. May cause an allergic skin reaction. Causes damage to organs through prolonged or repeated exposure. Harmful if swallowed.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazardous ingredients

: 2-piperazin-1-ylethylamine; 4-tert-butylphenol; m-phenylenebis(methylamine); Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia





Hazard statements (CLP)

: H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H361 - Suspected of damaging fertility or the unborn child.

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Precautionary statements (CLP)	: H372 - Causes damage to organs through prolonged or repeated exposure. H411 - Toxic to aquatic life with long lasting effects. : P260 - Do not breathe Vapours, Mist, Spray. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear eye protection, protective clothing, Wear respiratory protection, protective gloves. P302+P350+P315 - IF ON SKIN : Gently wash with plenty of soap and water. Get immediate medical advice / attention P310 - Immediately call a doctor, a POISON CENTER. P501 - Dispose of contents and container to an approved waste disposal plant.
EUH-statements	: EUH071 - Corrosive to the respiratory tract.
Labelling according to: exemption for packages of a capacity of 125ml or less	
Hazard pictograms (CLP)	:     GHS05 GHS07 GHS08 GHS09
Signal word (CLP)	: Danger
Hazardous ingredients	: 2-piperazin-1-ylethylamine; 4-tert-butylphenol; m-phenylenebis(methylamine); Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia
Hazard statements (CLP)	: H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H361 - Suspected of damaging fertility or the unborn child. H372 - Causes damage to organs through prolonged or repeated exposure.
Precautionary statements (CLP)	: P260 - Do not breathe Vapours, Mist. P264 - Wash hands, forearms and face thoroughly after handling. P280 - Wear protective gloves, protective clothing, eye protection. P310 - Immediately call a POISON CENTER or doctor. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. P302+P350+P315 - IF ON SKIN : Gently wash with plenty of soap and water. Get immediate medical advice / attention
EUH-statements	: EUH071 - Corrosive to the respiratory tract.

2.3. Other hazards

Other hazards not contributing to the classification : Without VOC (volatile organic compounds).

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	Conc. (% w/w)	Classification according to Regulation (EC) No. 1272/2008 [CLP] with its amendment Regulation (EU) 2016/1179
Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia	(CAS-No.) 9046-10-0 (EC-No.) 618-561-0 (REACH-no) 01-2119557899-12	< 50	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314 Aquatic Chronic 3, H412
m-phenylenebis(methylamine)	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5 (REACH-no) 01-2119480150-50	< 30	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
4-tert-butylphenol	(CAS-No.) 98-54-4 (EC-No.) 202-679-0 (EC Index-No.) 604-090-00-8 (REACH-no) 01-2119489419-21	< 30	Skin Irrit. 2, H315 Eye Dam. 1, H318 Repr. 2, H361f Aquatic Chronic 1, H410

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

2-piperazin-1-ylethylamine	(CAS-No.) 140-31-8 (EC-No.) 205-411-0 (EC Index-No.) 612-105-00-4 (REACH-no) 01-2119471486-30	< 30	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1B, H314 Skin Sens. 1, H317 Repr. 2, H361 STOT RE 1, H372 Aquatic Chronic 3, H412
2,4,6-tris(dimethylaminomethyl)phenol	(CAS-No.) 90-72-2 (EC-No.) 202-013-9 (EC Index-No.) 603-069-00-0 (REACH-no) 01-2119560597-27	< 10	Acute Tox. 4 (Oral), H302 Skin Corr. 1C, H314
Bis[(dimethylamino)methyl]phenol	(CAS-No.) 71074-89-0 (EC-No.) 275-162-0	< 3	Skin Corr. 1B, H314

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: Wash skin thoroughly with mild soap and water. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting without medical advice. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard. Presents no particular fire or explosion hazard.
Hazardous decomposition products in case of fire	: For further information, refer to section 10 : "Stability and Reactivity".

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Prevent fire fighting water from entering the environment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Provide adequate ventilation.
------------------	---------------------------------

6.1.1. For non-emergency personnel

Emergency procedures	: Evacuate unnecessary personnel. Do not breathe Vapours, Mist, Spray. Only qualified personnel equipped with suitable protective equipment may intervene.
----------------------	--

6.1.2. For emergency responders

Protective equipment	: Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Notify authorities if product enters sewers or public waters.

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
- Methods for cleaning up : Take up liquid spill into absorbent material. Sweep or shovel spills into appropriate container for disposal. Notify authorities if product enters sewers or public waters.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". Concerning disposal elimination after cleaning, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Concerning personal protective equipment to use, see section 8. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Avoid contact during pregnancy/while nursing. Do not breathe Vapours, Mist, Spray. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Avoid extremely high (> 50 °C) or low (<5 °C) temperatures. Keep only in the original container in a cool well ventilated place. Keep container closed when not in use. Store locked up.
- Incompatible products : acids.
- Storage temperature : 20 °C ± 10 °C
- Heat and ignition sources : Keep away from heat and direct sunlight.

7.3. Specific end use(s)

Industrial. Professional.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available.

8.2. Exposure controls

Appropriate engineering controls:

Provide local exhaust or general room ventilation to minimize vapour concentrations. Ensure good ventilation of the work station.

Personal protective equipment:

Gloves. Protective goggles. Protective clothing. [In case of inadequate ventilation] wear respiratory protection.

Hand protection:

Wear suitable gloves resistant to chemical penetration. Chemical resistant gloves (according to European standard NF EN 374 or equivalent).

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves, Reusable gloves	nitrile rubber (NBR), Polyvinylchloride (PVC)	6 (> 480 minutes)	≥0,11		EN 374

Eye protection:

Protective goggles. DIN EN 166

Skin and body protection:

Wear suitable protective clothing. CEN : EN 340; EN 369; EN 465

Respiratory protection:

[In case of inadequate ventilation] wear respiratory protection. EN 143

Device	Filter type	Condition	Standard
breathing apparatus with filter	Type P2	Vapour protection, Protection for Liquid particles	EN 143

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179



Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Colourless.
Odour	: characteristic.
Odour threshold	: No data available.
pH	: No data available.
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: < 0 °C
Freezing point	: No data available.
Boiling point	: > 100 °C
Flash point	: > 62 °C
Auto-ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: > 1 (air=1)
Relative density	: 1,05
Solubility	: In water, material is partially soluble.
Log Pow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known.

10.4. Conditions to avoid

Avoid extremely high (> 50 °C) or low (<5 °C) temperatures. Keep away from heat and direct sunlight.

10.5. Incompatible materials

acids.

10.6. Hazardous decomposition products

No additional information available.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Oral: Harmful if swallowed.

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ATE oral	769,644 mg/kg bodyweight
----------	--------------------------

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

LD50 oral rat	480 mg/kg
---------------	-----------

LD50 dermal rabbit	2090 mg/kg
--------------------	------------

m-phenylenebis(methylamine) (1477-55-0)

LD50 oral rat	930 mg/kg (Rat)
---------------	-----------------

LC50 inhalation rat (mg/l)	2,4 mg/l/4h (Rat)
----------------------------	-------------------

2-piperazin-1-ylethylamine (140-31-8)

LD50 oral rat	2140 mg/kg
---------------	------------

LD50 dermal rat	2250 ml/kg
-----------------	------------

LD50 dermal rabbit	866 mg/kg
--------------------	-----------

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Serious eye damage, category 1, implicit

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

STOT-single exposure : Not classified

STOT-repeated exposure : Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

LC50 fishes 1	> 100 mg/l
---------------	------------

EC50 Daphnia 1	15 mg/l
----------------	---------

EC50 72h algae (1)	135 mg/l
--------------------	----------

m-phenylenebis(methylamine) (1477-55-0)

LC50 fish 2	> 100 mg/l (LC50; 96 h)
-------------	-------------------------

EC50 Daphnia 1	16 mg/l (EC50; 48 h)
----------------	----------------------

Threshold limit algae 1	12 mg/l (EC50; 72 h)
-------------------------	----------------------

12.2. Persistence and degradability

DRY FLEX® 4 - Component B

Persistence and degradability	Not established.
-------------------------------	------------------

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

Persistence and degradability	Biodegradability in soil: no data available.
-------------------------------	--

m-phenylenebis(methylamine) (1477-55-0)

Persistence and degradability	not readily degradable in water.
-------------------------------	----------------------------------

12.3. Bioaccumulative potential

DRY FLEX® 4 - Component B

Bioaccumulative potential	Not established.
---------------------------	------------------

Reaction products of di-, tri- and tetra-propoxylated propane-1,2-diol with ammonia (9046-10-0)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

m-phenylenebis(methylamine) (1477-55-0)

BCF fish 1	< 2,7 (BCF)
------------	-------------

Log Pow	0,15
---------	------

Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
---------------------------	--

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

DRY FLEX® 4 - Component B

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.






Additional information : Empty containers should be taken for recycle, recovery or waste in accordance with local regulation.

Ecology - waste materials : Avoid release to the environment.

European List of Waste (LoW) code : 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
2735	2735	2735	2735	2735
14.2. UN proper shipping name				
AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE))	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))	AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine))
UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, III, (E), ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (M-PHENYLENEBIS(METHYLAMINE)), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, III, ENVIRONMENTALLY HAZARDOUS	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (m-phenylenebis(methylamine)), 8, III, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
8	8	8	8	8
				
14.4. Packing group				
III	III	III	III	III
14.5. Environmental hazards				
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes	Dangerous for the environment : Yes
No supplementary information available.				

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : C7
Special provisions (ADR) : 274
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T7

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Portable tank and bulk container special provisions (ADR) : TP1, TP28
Tank code (ADR) : L4BN
Vehicle for tank carriage : AT
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Hazard identification number (Kemler No.) : 80
Orange plates :



Tunnel restriction code (ADR) : E
EAC code : 2X
APP code : B

- Transport by sea

Special provisions (IMDG) : 223, 274
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T7
Tank special provisions (IMDG) : TP1, TP28
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Stowage category (IMDG) : A
Segregation (IMDG) : SG35
Properties and observations (IMDG) : Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.
MFAG-No : 153

- Air transport

PCA Excepted quantities (IATA) : E1
PCA Limited quantities (IATA) : Y841
PCA limited quantity max net quantity (IATA) : 1L
PCA packing instructions (IATA) : 852
PCA max net quantity (IATA) : 5L
CAO packing instructions (IATA) : 856
CAO max net quantity (IATA) : 60L
Special provisions (IATA) : A3
ERG code (IATA) : 8L

- Inland waterway transport

Classification code (ADN) : C7
Special provisions (ADN) : 274
Limited quantities (ADN) : 5 L
Excepted quantities (ADN) : E1
Carriage permitted (ADN) : T
Equipment required (ADN) : PP, EP
Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : C7
Special provisions (RID) : 274
Limited quantities (RID) : 5L
Excepted quantities (RID) : E1
Packing instructions (RID) : P001, IBC03, LP01, R001

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Mixed packing provisions (RID)	: MP19
Portable tank and bulk container instructions (RID)	: T7
Portable tank and bulk container special provisions (RID)	: TP1, TP28
Tank codes for RID tanks (RID)	: L4BN
Transport category (RID)	: 3
Special provisions for carriage – Packages (RID)	: W12
Colis express (express parcels) (RID)	: CE8
Hazard identification number (RID)	: 80

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Directive 2012/18/EU (SEVESO III) : E2 Hazardous to the Aquatic Environment in Category Chronic 2

15.1.2. National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Revised safety data sheet in accordance with commission regulation (EU) No 2016/1179.

Section	Changed item	Change	Comments
	Revision date	Modified	
	Supersedes	Modified	
2	Labelling according to: exemption for packages of a capacity of 125ml or less	Added	
2.2	EUH-statements	Added	
2.2	Precautionary statements (CLP)	Modified	
11.1	ATE oral	Modified	

Abbreviations and acronyms:

SDS	Safety Data Sheet
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
LC50	Median lethal concentration
LD50	Median lethal dose
CAS	CAS (Chemical Abstracts Service) number
EG-nr	EINECS- en ELINCS-number
EINECS	European Inventory of Existing Commercial Substances
OEL	Occupational Exposure Limit

Data sources : according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179.

DRY FLEX® 4 - Component B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2016/1179

Other information

: REACH Disclaimer:

This information is based on current knowledge. Consistency of data in the SDS with CSR is considered, as far as the information is available at the time of compilation (cfr Revision date and Version number). **DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Oral)	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Skin Sens. 1	H317	Calculation method
Repr. 2	H361	Calculation method
STOT RE 1	H372	Calculation method
Aquatic Chronic 2	H411	Calculation method

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product