

SAFETY DATA SHEET

FONTEDUR HB 80

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: FONTEDUR HB 80
Product code	: 156-s
Product description	: A two-component waterborne polyurethane paint.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor	
Tikkurila Oyj P.O. Box 53 FI-01301 VANTAA FINLAND Telephone +358 20 191 2000	
e-mail address of person responsible for this SDS	Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

1.4 Emergency telephone number

Telephone number	: 1 (2	12 24h)	
Supplier or Manufacturer			
Telephone number		ikkurila Oyj 358 20 191 2000	Mon-Fri 8-16

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS] Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 Label elements

Hazard pictograms



	•
Signal word	: Warning
Hazard statements	: H319 - Causes serious eye irritation.
Precautionary statements	
General	: Not applicable.
Prevention	: 🗗261 - Avoid breathing mist/spray.
Response	: P305 + P351 - IF IN EYES: Rinse cautiously with water for several minutes.
Storage	: Not applicable.

Date of issue/Date of revision	12.07.2016 Date of previous issue	21.04.2015.	FONTEDUR HB 80	
Disposal	: Not applicable.			
Supplemental label elements	: Not applicable.			

2.3 Other hazards

Other hazards which do : None known. not result in classification

SECTION 3: Composition/information on ingredients

3.2 Mixtures	: Mixture			
			Classification	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
otyl glycol acetate	REACH #: 01-2119475112-47 EC: 203-933-3 CAS: 112-07-2 Index: 607-038-00-2	≤3	Acute Tox. 4, H312 Acute Tox. 4, H332	-
n-butanol	REACH #: 01-2119484630-38 EC: 200-751-6 CAS: 71-36-3 Index: 603-004-00-6	<3	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335 STOT SE 3, H336	-
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

SECTION 4: First aid measures

4.1 Description of firs	t aid measures
General	: In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.
Eye contact	 Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.
Inhalation	: Remove to fresh air.
Skin contact	 Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	 If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious). If significant amounts have been swallowed or if symptoms persist, seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye irritation.

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of any immediate medical attention and special treatment needed

None.

12.07.2016 Date of previous issue 21.04.2015.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing : Use an extinguishing agent suitable for the surrounding fire. Recommended: media Alcohol resistant foam, CO2, powders or water spray/mist. Unsuitable extinguishing : Do not use a direct water jet that could spread the fire. media 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture	This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous thermal decomposition products	When exposed to high temperatures, may produce hazardous decomposition products, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

5.3 Advice for firefighters

Special protective actions for fire-fighters	:	Use water spray to keep fire-exposed containers cool. Do not release runoff from fire to drains or watercourses.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures	: Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	: Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling	: Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product.
7.2 Conditions for safe storage, including any incompatibilities	: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.
7.3 Specific end use(s)	: None.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
butyl glycol acetate	EU OEL (Europe, 12/2009). Absorbed through skin. Notes: list of indicative occupational exposure limit values TWA: 20 ppm 8 hours. TWA: 133 mg/m ³ 8 hours. STEL: 50 ppm 15 minutes. STEL: 333 mg/m ³ 15 minutes.

procedures

Recommended monitoring : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

21.04.2015.

DNELs/DMELs

No DNELs/DMELs available.

PNECs

No PNECs available.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn (see Personal protection for both components). Comply with the health and safety at work laws.

Individual protection measures

Eye/face protection	: Use safety eyewear (EN166), especially during spray-application.
Hand protection	 Wear protective gloves. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves
Skin protection	: Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	: If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a respirator with type P2 filter during sanding (EN149:2001). Be sure to use an approved/certified respirator or equivalent. Check that mask fits tightly and change filter regularly.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	
Physical state	: Liquid.
Color	: Coloured
Odor	: Mild.
Odor threshold	: Not relevant for the hazard assessment of the product.
рН	: Not relevant for the hazard assessment of the product.
Melting point/freezing point	: Not available.
Initial boiling point and	: Not available.
boiling range	
Flash point	: >100 °C
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not applicable. Product is a liquid.

Date of issue/Date of revision	12.07.2016 Date of previous issue	21.04.2015.	FONTEDUR HB 80	
Upper/lower flammability or explosive limits	: Not available.			
Vapor pressure	: Not available.			
Vapor density	: Not available.			
Density	: 1,3 to 1,4 g/cm ³			
Solubility(ies)	: Miscible in water.			
Partition coefficient: n-octanol/ water	: Not available.			
Auto-ignition temperature	: Not available.			
Decomposition temperature	: Not relevant for the hazard as	sessment of the	product.	
Viscosity	: Not relevant for the hazard as	sessment of the	product.	
Explosive properties	: No explosive ingredients pres	ent.		
Oxidizing properties	: No oxidizing ingredients prese	ent.		

9.2 Other information

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity	:	See Section 10.5.
10.2 Chemical stability	:	Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	:	Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	:	Avoid extreme heat and freezing.
10.5 Incompatible materials	:	Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis
10.6 Hazardous decomposition products	:	When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
butyl glycol acetate	LD50 Dermal	Rabbit	1500 mg/kg	-
n-butanol	LD50 Oral	Rat	790 mg/kg	-

Not classified.

Irritation/Corrosion

Causes serious eye irritation.

Sensitization

Not classified.

Mutagenicity

Not classified.

Carcinogenicity

21.04.2015. F

FONTEDUR HB 80

Not classified.	
Reproductive toxicity	
Not classified.	
Teratogenicity	
Not classified.	
Specific target organ toxicity (single exposure)	
Not classified.	
Specific target organ toxicity (repeated exposure)	
Not classified.	
Aspiration hazard	
Not classified.	

SECTION 12: Ecological information

Ecological testing has not been conducted on this product. Do not allow to enter drains, water courses or soil.

The product is not classified as environmentally hazardous according to Regulation (EC) 1272/2008.

12.1 Toxicity Not available.	:	No specific data.
12.2 Persistence and degradability	:	No specific data.
12.3 Bioaccumulative potential	:	No specific data.
12.4 Mobility in soil		
Soil/water partition coefficient (Koc)	:	Not available.
Mobility	:	Not available.
12.5 Results of PBT and vPvE	3 a	ssessment
РВТ	:	Not applicable.
vPvB	:	Not applicable.

12.6 Other adverse effects : Not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

```
Product
```

```
Methods of disposal
```

: Gather residues into waste containers. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

Packaging

Methods of disposal

: Empty packaging should be recycled or disposed of in accordance with national regulations.

Date of issue/Date of revision	12.07.2016 Date of previous issue	21.04.2015.	FONTEDUR HB 80
Special precautions	: Note! The hardener reacts with w The ready for use mixture of pain closed containers can result in pr	t and hardener v	

SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	ΙΑΤΑ
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk	1	Not available.
according to Annex II of		
MARPOL and the IBC Code		

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations Europe inventory

- : Not determined.
- **15.2 Chemical Safety** : This product contains substances for which Chemical Safety Assessments are still Assessment required.

SECTION 16: Other information

Indicates information that	has changed from previously issue	ed version.	
Abbreviations and acronyms	CLP = Classification, Labelling 1272/2008] DMEL = Derived Minimal Effe	 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level 	
	EUH statement = CLP-specifi PBT = Persistent, Bioaccumu PNEC = Predicted No Effect (RRN = REACH Registration N vPvB = Very Persistent and V	ic Hazard statement lative and Toxic Concentration Number	
	e classification according to Reg fication	gulation (EC) No. 1272/2008 [CLP/GHS] Justification	

Eye Irrit. 2, H319

Calculation method

Full text of abbreviated H	: 🗾 226 Flammable liq	P26 Flammable liquid and vapor.	
statements	H302 Harmful if swa	2 Harmful if swallowed.	
	H312 Harmful in contact with skin.		
	H318 Causes serious eye damage.H319 Causes serious eye irritation.		
	H319 Causes senous eye inflation. H332 Harmful if inhaled.		
	H335 May cause respiratory irritation.		
	5	, , ,	
Full text of classifications	: Acute Tox. 4, H302	ACUTE TOXICITY (oral) - Category 4	
[CLP/GHS]	Acute Tox. 4, H312	ACUTE TOXICITY (dermal) - Category 4	
	Acute Tox. 4, H332	ACUTE TOXICITY (inhalation) - Category 4	
	Eye Dam. 1, H318	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	
	Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2 FLAMMABLE LIQUIDS - Category 3	
	Flam. Liq. 3, H226 Skin Irrit. 2, H315	SKIN CORROSION/IRRITATION - Category 2	
	STOT SE 3, H335	SPECIFIC TARGET ORGAN TOXICITY (SINGLE	
	0101020,1000	EXPOSURE) (Respiratory tract irritation) - Category 3	
	STOT SE 3, H336	SPECIFIC TÁRGET ORGAN TOXICITY (SINGLE	
		EXPOSURE) (Narcotic effects) - Category 3	
Date of issue/ Date of revision	: 12-07-2016		
Date of previous issue	: 21-04-2015		
Version	: 1.01		
Notice to reader			

21.04.2015.

FONTEDUR HB 80

12.07.2016 Date of previous issue

Notice to reader

Date of issue/Date of revision

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.