

HICKSON DECOR ANTISLIP

DESCRIPTION

Decor Antislip is a solvent based, medium build, self priming clear coating. It is a clear protective coating for brush application onto unweathered pressure preservative treated decking timbers or exterior wood flooring. For maximum protection use with Décor Wood Stain to provide UV protection, abrasion resistance and antislip. anti-slip

Containing micro-aggregate particles, this coating gives increased grip in wet conditions by providing water droplet repellence and creating a textured surface, while allowing the beauty of the wood to show through. It also gives some protection to bare timber from the ageing effects of sun and rain. To provide extended durability apply onto timber pre-coated with one of the Hickson Decor Woodstain shades.

ideal to use on • patios • decking • utility rooms • steps • jetties • swimming pools
unique qualities • water repellent • reduces slippery conditions

AREAS OF USE

On new (clean and dry) pressure preservative treated timber and decking in external situations.

MAIN FEATURES

- Provides a highly water repellent finish
- Reduces the timber's capacity to retain water
- Contains abrasive particles to give a textured, hard wearing surface coating
- Helps provide sure footing and reduce slippery conditions in wet weather
- limits the growth of organisms that can cause slippery conditions

SURFACE PREPARATION

Remove any dirt, dust, oil or grease. Surface must be dry.

New surfaces – no other preparation.

Weathered surfaces – sand down to clean, sound, treated wood (use dust mask if using sanding equipment with no dust collect)on).

Previously painted or stained surfaces – any old coating must be clean and in sound condition. Lightly sand to 'key the surface.

Decking systems - apply two coats of Wood stain prior to the application of Decor Antislip coating. This will ensure a professional level of protection.

METHODS OF APPLICATION

One liberal coat. Allow time for absorption along the grain of the timber.

By brush, short haired roller or 'vee' applicator only. On grooved decking care must be taken to ensure that the coating adheres to the ridge of the timber and is not 'lost' in the groove. Roller application is recommended in this situation. Take care not to overapply and leave thick 'pooled' layers of the coating as these may not fully cure and may result in a cloudy appearance after rain.

Mix thoroughly before and during use.

MAINTENANCE AND CLEANING

When required, every 1-2 years, depending on the level and nature of the traffic on the flooring. When wear through to the substrate has occurred, it is only necessary to touch up the worn area. Always remove leaves and decaying vegetation from the surface decking as soon as possible in order to retain the benefits of the Decor Antislip surface.

Clean brushes and spillages with white spirit. Remove as much paint as possible from brush before washing. Some Local Authorities have special facilities for disposing of waste coatings. Do not empty paint into drains and watercourse. Do not use white spirit on skin. A proprietary hand cleaner should be used.

Protect from extremes of temperature during storage and application.

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk

CAUTION

Always apply to a test area before starting work. Appearance may vary according to the colour and type of wood and the number of coats.

COVERAGE

11-18 square metres per litre, depending on substrate

DRYING TIME

Touch dry 3-5 hours. Allow 24 hours between coats.

PACKAGING

available in: 1 litre, 2.5 litre.

STORAGE

Store in unopened containers in a cool dry place away from direct sunlight.

HEALTH SAFETY AND THE ENVIROMENT

DANGER: Flammable liquid and vapour. May be fatal if swallowed and enters airways. May cause drowsiness and dizziness. Harmful to aquatic life with long lasting effects. Avoid release into the environment.

Read all instructions before use. Keep out of reach of children. Not recommended for interior use on large surface areas. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking. Use explosion-proof electrical, ventilating, lighting and all materialhandling equipment. Contaminated cloths may self ignite without warning. Dispose of after soaking in water.

Use only in well ventilated areas. Wear protective gloves. Wear eye or face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. **IF**

SWALLOWED: Immediately seek medical attention. Do NOT induce vomiting. **IF ON**

SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower, do not use solvent, thinners or white spirit. If medical advice is needed, have product container or label at hand.

Remove excess from tools and mixing vessels before cleaning with white spirits.

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application

Date of issue: January 2019

Further information may be obtained from:

Polyvine Limited, Vine House, Cheddar Business Park, Wedmore Road, Cheddar, BS27 3EB

Tel 01934 740305 • www.polyvine.com • email info@polyvine.co.uk