



TIKKURILA

## HOMEENPOISTO

MOULD REMOVAL FOR WOODEN AND MASONRY SURFACES.

### DESCRIPTION

Gel-like hypochlorite solution.

### RECOMMENDED USES

Untreated and painted moldy exterior surfaces.

### PRODUCT FEATURES

For removing mold from painted and unpainted wood, rendered and concrete surfaces before new or maintenance painting, and from concrete tile and fiber cement roofs before maintenance painting.

# HOMEENPOISTO

## TECHNICAL DATA

<b>Coverage</b>	Depends on the cleaning requirement.
<b>Can sizes</b>	1 l, 5 l
<b>Thinner</b>	Water
<b>pH value</b>	Dilute solution approx. 12.
<b>Application method</b>	Spray, sponge or brush.
<b>Density (kg/l)</b>	Approx. 1.1 kg/l, ISO 2811
<b>Storage</b>	Protect from frost



# HOMEENPOISTO

## APPLICATION INSTRUCTIONS

### Mixing components

Dilute Mould Removal with water, mixing ratio 1:3.

### Surface preparation

Protect glass, aluminum and other similar surfaces that could be damaged by the detergent. Take care not to splash the product on clothes and, for example, untreated furniture. The product is bleaching.

### Application

Dilute Tikkurila Homeenpoisto with water to a ratio of 1:3. Apply the diluted mixture on the moldy facade from the bottom up with a sponge, soft brush or, for large areas, a garden hose. Cleaning from the top down can leave streaks on the facade. Let the solution act for about 30 minutes. You can leave the solution on for longer if the substrate is very moldy. Use a brush if necessary. After the treatment, rinse the surfaces carefully with clean water from the top down, e.g. with a hose.

Prime unpainted wood surfaces immediately with Valtti Pohjuste or Valtti Plus Base before treating the surface. Give previously painted surfaces a maintenance coat.

### Cleaning of tools

Clean tools with water.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.