



TIKKURILA

LUJA KOSTEUSSULKU

MOISTURE STOP WHICH FORMS AN IMPERVIOUS SURFACE

DESCRIPTION Water-borne moisture stop which gives a very impervious surface.

RECOMMENDED USES Interior wall and ceiling surfaces.

PRODUCT FEATURES For interior use. Suitable for surfaces treated with Tikkurila Presto LV Märkätilatasoite, different types of wallboards, fiberglass wallpaper, etc.



LUJA KOSTEUSSULKU

TECHNICAL DATA

Colour Shades	Translucent green.
Coverage	Approx. 4–6 m ² /l in two coats, undiluted.
Can sizes	3 l, 10 l
Application method	Roller, brush or spray application.
Drying time (23°C and 50% relative air humidity)	Touch-dry in approx. 4 hours. Can be finished with Luja finishing paint after approx. 4 hours.
Density (kg/l)	Approx. 1.2 kg/l, ISO 2811
Volume solids (%)	39
Storage	Protect from frost. Badly closed or short cans endure badly long-time storage.



LUJA KOSTEUSSULKU

APPLICATION INSTRUCTIONS

Application conditions

The surface to be painted must be dry, the ambient temperature at least +10 °C and the relative humidity of air below 80%.

Surface preparation

Clean the surfaces by removing any dirt and dust. If the substrate has mold damage, find out the cause and repair the damage carefully before painting. Remove any loose, flaking paint with a scraper. Remove vinyl wall coverings and ceramic tiles completely. Sand glossy paint surfaces to a matte finish. Wash the surface with Maalipesu if necessary and rinse carefully with water. Level concrete, rendered and other surfaces with Presto LV Märkätilatasoite. Sand the dried surface and wipe off the sanding dust.

Application

Stir Luja Kosteussulku well before use. Apply two coats of moisture barrier with a roller. Ensure coverage at corners and lead-throughs by applying moisture barrier with a brush. Let dry for 1–4 hours between applications. Finish with Luja finishing paint after approx. 4 hours from the second application of moisture barrier.

Cleaning of tools

Clean tools with water. Tikkurila Pensselipesu Tool Cleaner is recommended to remove slightly hardened paint.

Environmental and waste disposal

Destroy liquid waste according to the local regulations for hazardous waste. Recycle empty, dry cans or dispose them of in accordance with local regulations.

HEALTH AND SAFETY LABELLING according to Regulation (EC) No. 1272/2008

Contains 1,2-benzisothiazol-3(2H)-one (BIT). May produce an allergic reaction. Wear protective gloves.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.