

TYPE	ECO-FLEX UNIVERSAL OIL 4433 is an aqueous emulsion of processed oils consisting mainly of vegetable-oil combinations.
USE	For treatment of furniture and fixtures and fittings where environmental considerations in connection with surface treatments are of decisive importance. Mainly utilised for pine wood, but is also suitable for other species of wood.
SPECIAL PROPERTIES	ECO-FLEX UNIVERSAL OIL 4433 excels by particularly good penetration and wetting providing good depth and at the same time very low fibre raising. The universal oil penetrates rapidly and leaves a comfortably smooth, uniform and dry surface. Items treated can be stacked down immediately after application without risk of blotch formation or other irregularities. In addition, ECO-FLEX UNIVERSAL OIL 4433 can be tinged with water borne stainers whereby a single treatment provides the same result as the traditional two-step treatment with staining followed by oil treatment.

TECHNICAL DATA

Delivery viscosity	Approx. 15-20 s DIN 4 at 20 °C.
Density	Approx. 1.0 kg/l
Solids, weight	Approx. 8 %
Volatile organic compound (VOC)	See Safety Data Sheet.
Storage	To be stored and transported at temperatures above 10 °C. To be shaken/stirred thoroughly before application. Storage: See label. Store in a tightly closed container.
Application method	Can be applied by spraying, dipping, coating or on rinser.
Drying method	Air.

DIRECTIONS FOR USE

Application data	The product is ready for use.
Cleaning	Tools to be cleaned in water or TEKNOCLEAN 1949.

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

ADDITIONAL INFORMATION	Should not be stored in metal containers as contact with metal may result in discoloration. In the event of tinged products, always make a test treatment for control of colour as variations in the own colour of the wood and structure and application technique utilised may provide a considerable colour difference in relation to approved sample
-------------------------------	--