



Öljypohja Oil Primer - Alkyd opaque wood primer

Description	Alkyd Oil Priming Paint for exterior painting of bare wood surfaces before finishing with oil or acrylate paints. Also suitable for painting surfaces previously treated with oil paint.
Product features	Öljypohja is an alkyd microporous wood primer suitable for application to new and previously painted timber prior to overcoating with Tikkurila topcoats. Öljypohja is fully tintable to topcoat colours.
Recommended uses	Exterior walls, window frames, railings, fences.



TECHNICAL DATA



Base paints	AP and C
Colour Range	White AP base paint can be tinted approximately to the colour of the finishing paint. Colours made from the C-base should be tinted to the same colour as the finishing paint. Colour accuracy is not perfect.
Gloss grade	Matt
Coverage	Sawn surfaces 5 - 8 m ² /l. Planed surfaces: 8 -10 m ² /l.
Can sizes	0.9 l, 2.7 l and 9 l
Thinner	White Spirit 1050
Application method	Brush
Drying time at 23°C and 50% relative air humidity	Recoatable after 24 hours. Drying time depends on conditions, absorption to the substrate and film thickness.
Solids volume	56 %
Density	1.4 kg/l, ISO 2811
Storage	Unaffected by cold storage. Poorly closed or short canisters do not resist long-term storage.
Product code	206_6201

APPLICATION DETAILS

Application conditions	The surface to be treated has to be dry i.e. the humidity of the wood has to be under 20 %. During painting and drying the temperature of the air should be at least +5°C and the relative humidity of the air under 80 %.
Preparation	Unpainted surfaces: Clean the surface from all dirt, mould and loose material. Prime the surface at earliest possible stage with Valtti Pohjuste or Valtti Akvabase priming oil. Touch up nail heads, and other rusting metal parts with Rostex Super Metal Primer. Remove loose resin from knots. Previously painted surfaces: Remove all loose material and grayed wood surface with a scraper and clean the



Öljypohja Oil Primer - Alkyd opaque wood primer

	surface with a steel brush. Wash down dirty and mould affected surfaces with Mould Removal (Homeenpoisto) or with Tehopesu Super Clean according to the instructions for use. Treat bare wooden surfaces with Valtti Pohjuste or Valtti Akvabase.
Finishing	Stir Öljypohja well before use and apply on bare wooden surfaces once by brush. Treat the end-grains with special care.
Cleaning of tools	Clean tools with White Spirit 1050 or with Tikkurila Pensselipesu (Tool Cleaner)
EU VOC 2004/42/EC-limit value	(cat A/g) 350g/l(2010) Öljypohja contains VOC max. 350g/l.

HEALTH AND SAFETY LABELLING

according to Regulation (EC) No. 1272/2008



GHS02



GHS07



GHS09

Contains: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics, 4,5-dichloro-2-octyl-2H-isothiazol-3-one and 2-octyl-2H-isothiazol-3-one.

Warning. Flammable liquid and vapor. May cause an allergic skin reaction. May cause drowsiness and dizziness. Toxic to aquatic life with long lasting effects.

Keep out of reach of children. If medical advice is needed, have product container or label at hand. Avoid breathing vapor. Wear protective gloves. Use only outdoors or in a well-ventilated area. Keep away from sparks and open flames. - No smoking. Avoid release to the environment. IF ON SKIN: Wash with plenty of soap and water. Contains small amounts of sensitizing substances: neodecanoic acid, cobalt salt, and ethyl methyl ketoxime. A Safety Data Sheet is available at request.

 [Safety Data Sheet - Öljypohja](#)

ENVIRONMENTAL and WASTE DISPOSAL

Avoid spillage into drains, water systems and soil. Recycle empty, dry cans or dispose them of in accordance with local regulations. Destroy liquid waste according to the local regulations for hazardous waste. Note! Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soaked in water and placed in a closed metal container before disposal.

TRANSPORT

3 III

sre180316 / akk210316 / ssa100308 / uha300403 / 206 6201