

Beissier

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : EXTERIOR QUICK DRY FILLER
Product code : 1440703025

1.2. Relevant identified uses of the substance or mixture and uses advised against

Powder coat for outdoor work.
For building application
For professional use
For professionals and DIY

Use descriptor system (REACH) :

SU: 19
SU: 22
SU: 21

1.3. Details of the supplier of the safety data sheet

Registered company name : BEISSIER SAS.
Address : Quartier de la gare.77760.LA CHAPELLE LA REINE.FRANCE.
Telephone : +33 1 60 39 61 10. Fax : +33 1 60 39 61 11.
beissier.fds@beissier.fr
www.beissier.fr

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA / <http://www.centres-antipoison.net>.

Other emergency numbers

Belgium :	Tel : 070/245.245
UK - National Poisons Information	44 / 191 22 5131
Service Phone :	
Poland :	(12) 411 99 99

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Serious eye damage, Category 1 (Eye Dam. 1, H318).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Eye irritation (Xi, R 36).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Contains Cement

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :
DANGER

Product identifiers :
EC 266-043-4 CIMENT PORTLAND

Hazard statements :
H318 Causes serious eye damage.

Precautionary statements - Prevention :
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements - Response :
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor/...

2.3. Other hazards

In use, may form flammable/explosive dust-air mixture.
The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>
The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.
In case of dust formation by mechanical action (sanding, sawing, etc ...), this dust may cause irritation by inhalation and contact with eyes.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Preparation based on hydraulic binder, sythétique binder fibers, mineral fillers and additives.

Composition :

Identification	(EC) 1272/2008	67/548/EEC	Note	%
INDEX: 65997_15_1	GHS07, GHS05	Xi	[1]	2.5 \leq x % < 10
CAS: 65997-15-1	Dgr	Xi;R37/38-R41		
EC: 266-043-4	Skin Irrit. 2, H315 Eye Dam. 1, H318			
CIMENT PORTLAND	STOT SE 3, H335			

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

Remove to fresh air
If breathing is irregular or stopped administer artificial respiration and call a doctor.

In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.
Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.
If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of splashes or contact with skin :

Watch out for any remaining product between skin and clothing, watches, shoes, etc.
Wash skin thoroughly with water
Do not use solvents or thinners

In the event of swallowing :

Seek medical attention, showing the label.
Keep at rest. Do not induce vomiting
Give nothing by mouth
If swallowed if the quantity is small (no more than a sip), rinse the mouth with water and consult a doctor

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

- In the event of a fire, use :
- sprayed water or water mist
 - powder
 - carbon dioxide (CO₂)

Unsuitable methods of extinction

- In the event of a fire, do not use :
- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

- Use self-contained breathing apparatus and protective clothing
- Prevent effluent from entering sewers or waterways
- Cool in closed containers exposed to fire.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- Consult the safety measures listed under headings 7 and 8.
- Ensure adequate ventilation
- In case of dust formation use a respirator with filter type P3.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Retrieve the product by mechanical means (sweeping/vacuuming) : do not generate dust.

6.4. Reference to other sections

Cf 8 & 13

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Anyone suffering from respiratory problems or allergies must not handle or be exposed to powdered paints

7.1. Precautions for safe handling

- Always wash hands after handling.
- Remove and wash contaminated clothing before re-using.
- Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.
- Use in a well ventilated area
- Avoid contact with skin and eyes.
- Avoid the flights of dust during the mixing of the product.

Fire prevention :

- Precautions must be taken to prevent any dust formation at a concentration higher than ignition or explosion concentration or the occupational exposure limits.
- Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.
- Keep packages tightly closed and away from sources of heat, sparks and naked flames.
- Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.
Avoid eye contact with this mixture at all times.
Packages which have been opened must be reclosed carefully and stored in an upright position.
Wear respiratory protection in case of insufficient ventilation (mask type P3).

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

Stock in accordance with the label.

Storage

Keep well away from all sources of ignition, heat and direct sunlight.
Keep away from frost and heat sources
The product contains cement to avoid contact with water.

Packaging

Always keep in packaging made of an identical material to the original.
After use, the containers should be closed and stored upright.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Care must be taken to comply with the statutory provisions of the Labour Code for all types of dust in the atmosphere (total, respirable alveolar)

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
65997-15-1	10 mg/m ³	-	-	-	-

- Germany - AGW (BAuA - TRGS 900, 21/06/2010) :

CAS	VME :	VME :	Excess	Notes
65997-15-1	-	5 mg/m ³ E	-	DFG

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
65997-15-1	10 mg/m ³	-	-	-	TI

8.2. Exposure controls**Personal protection measures, such as personal protective equipment**

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Before handling powders or dust emission, wear mask goggles in accordance with standard EN166.
Prescription glasses are not considered as protection.
Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.
Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.
Gloves must be selected according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
Type of gloves recommended :
- Natural latex
Recommended properties :
- Impervious gloves in accordance with standard EN374

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Avoid breathing dust.

Type of FFP mask :

Wear a disposable half-mask dust filter in accordance with standard EN149.

Category :

- FFP3

During the preparation of the coating, in case of sanding and / or dry film stripping, there may be dust formation. In this case the wearing of appropriate respiratory protection is recommended (mask P3).

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties****General information :**

Physical state :	Powder or dust.
Color:	White
Odour:	Low emission level

Important health, safety and environmental information

pH :	Not stated.
	Neutral.
pH (aqueous solution) :	11.3
Boiling point/boiling range :	Not specified.
Flash point interval :	Not relevant.
Vapour pressure (50°C) :	Not relevant.
Density :	> 1
Water solubility :	Insoluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

Exothermic reaction in the presence of water when taking the product.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- formation of dusts

Dusts can form an explosive mixture with air.

10.5. Incompatible materials

Keep away from :

- strong oxidising agents

- strong reducing agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

- calcium oxide

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

Powdered paints may cause local skin irritation, in folds in the skin or on contact with tight clothing (too tight fitting)

11.1.1. Substances

No toxicological data available for the substances.

11.1.2. Mixture

Skin corrosion/skin irritation :

A prolonged or repeated contact with skin or mucous membranes may cause irritation, redness, dermatitis ...

Serious damage to eyes/eye irritation :

Splashes may cause irritation and reversible damage

Respiratory or skin sensitisation :

when sanding, there may be formation of dust. Prolonged inhalation may cause an irritation of the throat, nose and lungs for sensitive people

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

All flow into drains or watercourses should be avoided.

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :

08 02 01 waste coating powders

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

- Container information:

No data available.

- Particular provisions :

This product is not covered by Directive 2004/42 / CE

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Reference : E0423

Title for H, EUH and R indications mentioned in section 3 :

H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
R 37/38	Irritating to respiratory system and skin.
R 41	Risk of serious damage to eyes.

Abbreviations :

SU 19 - Building and construction work

SU 21 - Consumer uses: Private households (= general public = consumers)

SU 22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion