



Product Selector

from the world leader in coatings for pre-coated metal

1 ASSESSMENT OF EXISTING CLADDING

2 PREPARATION OF CLADDING PRIOR TO REPAINTING WITH STEELSEAL®

3 REPAINT WITH STEELSEAL®

EXISTING COATING	CONDITION	FUNGICIDAL WASH	DETERGENT/WATER WASH	REMOVAL OF LOOSE PAINT	REMOVAL OF CORROSION PRODUCTS	ABRASION OF EXISTING COATING SERVICE	SOLVENT WIPE	PATCH PRIME ANY BARE METAL	PRIMER COAT	UNDERCOAT	TOPCOAT	
								STEELSEAL® PRODUCT CODES				
								PC4VC	PC4VC	PC4WO	PC5AS	PC5VF
PVC Plastisol	'New' (< 1 year)	○	●				●		●		●	
	Weathered, Firmly Adhering	○	●	○	○			○	●		●	
	Peeling/Flaking	○	○	●	●			●	●		●	
	Previously Overpainted	○	●	○	○	●		○	○	●	●	
Polyester, Silicone Polyester, PVDF	'New' (< 1 year)	○	●			●			●		●	
	Weathered, Firmly Adhering	○	●	○	○			○	●		●	
	Peeling/Flaking	○	○	●	●			●	●		●	
	Previously Overpainted	○	●	○	○	●		○	○	●	●	

● ● Required
○ ○ May be needed

This table is for indication only. Please contact Akzo Nobel for specifications tailored to your project.

An Etch Primer for applications on aluminium alloys is also available.

All products must be used in accordance with the relevant Product Data Sheets and Safety Data Sheets (available on request from Akzo Nobel).