

WV 802



sikkens
WOOD COATINGS

Product description

Waterbased maintenance milk to protect and refresh weathered paint surfaces on windows. Regular use prolongs the renovation intervals.

- water and dirt resistant
- quick drying
- easy to apply
- good weather resistance
- good colour and gloss refresher

Colour

Colourless

Gloss level

Gloss

Binder type

Watery polymer

Density (specific weight)

approx. 1.00 - 1.03 kg/l

Packaging

250 ml

Processing

The paint surface which should be maintained has to be cleaned thoroughly with a suitable household cleaning agent and afterwards with the special cleaner for deeper cleaning. When the surface is fully dried the maintenance milk is applied with a sponge quickly, but evenly on the paint surface. Before use of the maintenance milk the bottle has to be shaken intensely. The matt maintenance milk is for matt and semi-matt surfaces, the glossy maintenance milk should be used for satin-gloss and glossy surfaces.

Consumption

Approx. 20 ml/m²

Application temperature

+10 - 30 °C for substrate, air and material at approx. 60 % R.H.

Drying

At standard atmosphere of 23 °C / 50 % relative humidity.
Dust dry: after approx. 10 - 20 minutes.

Cleaning of equipment

Clean with water immediately after use and, if required, add some commercially available washing-up liquid or ST 830.

Storage

The minimum shelf life in the unopened original container is two years; Storage temperature +5 - +30 °C.
After expiry of the BBD, the product may still be processable, but the product properties may differ from "fresh" material. For that reason, the user must apply expired material with particular attention.
Started containers must be closed carefully! Store in a cool but frost-free place.

Disposal

Only empty containers may be recycled. Dispose of material residues according to local regulations. The EC waste code applicable to such material is: 08 01 12

Safety Data Sheet

Further data in the Material Safety Data Sheet according to 91/155/EEC
www.sikkens-wood-coatings.com Downloads Safety Data Sheets

Warning

Before use, read the identification and product information. Always follow customary protection measures, even when working with low emission products.

General instructions

Through the application of maintenance milk, painted surfaces obtain the original freshness. With regular use (1-2 yearly in spring and autumn), the durability of the coating system rises and maintenance periods can be extended. Defect coating systems cannot be repaired with maintenance milk. The correct products are referred to on the technical data sheets.

Notes

The gloss level of the surface might be changed by the maintenance milk.

Coating recommendation

Before the maintenance coating, the surface has to be sanded thoroughly and cleaned with the special cleaner. The maintenance coat should be carried out Sikkens renovation products.

Drying times

Drying at:	Standard atmosphere: 23 °C / 50% rel. humidity	Forced at 40 °C
Dust dry		
Sandable		
Recoatable		

Products from AkzoNobel Wood Coatings are exclusively produced for professional and industrial users, who have a basic knowledge of the handling and application of chemical/technical products for surface design. The processing instructions for reaching the qualities given in the leaflets should be regarded as non-binding recommendations and do not constitute any warranty. These recommendations are based on our experiences, including test series, and should facilitate and promote the work of our clients. Any potential deviation from ideal working conditions is within the responsibility of our clients and may affect the (end) result of the application. The purchaser is not relieved from his duties to inspect the product and its suitability for the surface to be processed, preferably through trial processing. If in any doubt as to the handling or processing of the purchased product, our material experts as well as our application and laboratory technicians will help you to the best of their ability.

AkzoNobel, of course, guarantees an impeccable quality of its products in its product specifications, yet the use thereof lies entirely within the responsibility of the purchaser. As long as we have not guaranteed – in writing – the specific characteristics and suitability of a product for a contractually agreed purpose, any advice or information given regarding the application or handling, even if the advice or information is given to the best of our knowledge, will not be binding nor will it constitute a warranty. AkzoNobel's liability for the use of its products by its customers is limited in its General Sales and Delivery Conditions, to which the purchaser is hereby referred. The applicable version of the Technical Data Sheet for this product can be downloaded from our websites. Previous versions of the Technical Data Sheets are rendered void with the issue of a new one. Date of issue: 2017-08-19

EMEA HQ

Akzo Nobel Hilden GmbH ● Düsseldorf Str. 96 - 100 ● 40721 Hilden ● Deutschland ● www.akzonobel.com/wood

AkzoNobel