

---

<b>TYPE</b>	One-component nitrocellulose based clear lacquer.
<b>USE</b>	For all types of wood and fibreboards. Only for interior use.
<b>SPECIAL PROPERTIES</b>	Very fast drying. Can be polished by hand or machine to a pleasant surface with high gloss. Scratch resistance.

---

**TECHNICAL DATA**

<b>Gloss (60°)</b>	80 units Gardner
<b>Delivery viscosity</b>	140-150 s, DIN-cup 4, 20°C
<b>Specific density</b>	0.92-1.00 kg/l.
<b>Solids</b>	Approx. 28 % by weight Approx. 20 % by volume
<b>Volatile organic compound (VOC)</b>	See Safety Data Sheet.
<b>Storage</b>	Storage: See label.
<b>System</b>	Can be used as primer and as topcoat. Recommended amount applied, 2 x 80-150 g/m <sup>2</sup> .

**DIRECTIONS FOR USE**

<b>Application method</b>	Conventional- and airless spraying.		
<b>Drying</b>		<u>20 °C</u>	<u>50 °C</u>
	Dry for handling	60 min.	30 min.
	Dry for stacking	2 hours	1 hour
<b>Thinner</b>	TEKNOSOLV 1135-93.		
<b>Cleaning</b>	TEKNOSOLV 1135-93.		

**HEALTH AND SAFETY** See Safety Data Sheet.