
TYPE	One component lacquer.
USE	For all types of wood and fibreboards. Only for interior use.
SPECIAL PROPERTIES	Very fast drying. Scratch resistance. No aromatics.

TECHNICAL DATA

Gloss (60°)	5-50 units Gardner
Viscosity	30-35 s, DIN-cup 4, 20 °C
Density	0.90-0.98 kg/l
Solids	Approx. 24 % by weight Approx. 17 % by volume
Volatile organic compound (VOC)	See Safety Data Sheet.
Storage	Storage: See label.
System	Can be used both as primer and as top coat. Recommended amount applied 2 x 80-150 g/m ² .

DIRECTIONS FOR USE

Application method	Conventional, automatic and high-pressure spraying and curtain coating.		
Drying		<u>20 °C</u>	<u>50 °C</u>
	Dry for handling	1 hour	30 min.
	Dry for stacking	2 hours	1 hour
Thinner	TEKNOSOLV 1135-93.		
Cleaning	TEKNOSOLV 1135-93.		

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.
