

---

<b>TYPE</b>	Water borne enamel based on acrylic/polyurethane with opaque pigments.
<b>USE</b>	Sprayable enamel for industrial use on primed surfaces or directly on plasterboards. Only for interior use.
<b>SPECIAL PROPERTIES</b>	The enamel has good application properties and good levelling properties. The cured enamel provides a rich and smooth surface, which is easy to clean.

---

**INSTRUCTION FOR USE**

<b>Gloss</b>	Approx. 10 depend on the character of the surface.
<b>Delivery viscosity</b>	25-30 s DIN 4.
<b>Density</b>	Approx. 1.20 kg/l
<b>Solids by weight</b>	Approx. 39 %
<b>Storage</b>	To be protected against frost.

**APPLICATION DETAILS**

<b>Application</b>	Airless spraying.
<b>Drying method</b>	IR- or convection oven.

<b>HEALTH AND SAFETY</b>	See Safety Data Sheet.
--------------------------	------------------------

---

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com).

---