

TECHNICAL DATA SHEET

2 12.04.2019

TEKNOCOAT AQUA SEALER 2700-0X

Water borne sealer

TYPE Water borne clear sealer for blocking discoloration of knots.

USE For furniture, panels etc. made of pine wood. Only for interior use.

SPECIAL PROPERTIES Prevents discoloration of knots.

Low pH. Low VOC.

Very important with careful cleaning of equipment before and after use.

TECHNICAL DATA

Density Approx. 1.03–1.08 kg/l

Solids Approx. 37–42 % by weight

Approx. 35-37 % by volume

Volatile organic compound

(VOC)

See Safety Data Sheet.

Storage: See label.

System TEKNOCOAT AQUA SEALER 2700-0X is applied in one layer, 90-120 g/m². Recoat

with a water borne translucent or opaque topcoat.

Only flatter or very slight sanding is recommended.

DIRECTIONS FOR USE

Application method Conventional spraying.

Airless spraying. Airmix spraying.

Drying times 20° C 20 min./ 50 °C

Dry for handling 1 h After cooling

Thinner Water

Cleaning Water

HEALTH AND SAFETY See Safety Data Sheet.

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.