
TYPE	Paste made of lightfast pigments and binders. The paste is mixable with most cellulose and acid-curing lacquers and thinners.
USE	To make transparent and opaque colours.
SPECIAL PROPERTIES	12 colours can be mixed. Thus it is possible to make every conceivable colour.

TECHNICAL DATA

Total mass of solids	Approx. 323-1643 g/l
Volatile organic compound (VOC)	See Safety Data Sheet.
Storage	Storage: See label. Store in a tightly closed container.

DIRECTIONS FOR USE

Application data	For transparent treatment add 1-5 % TEKNOCOAT TINTER and for opaque treatment 10-20 % TEKNOCOAT TINTER, depending on the colour.
-------------------------	---

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

ADDITIONAL INFORMATION	To be added to the lacquer while stirring prior to the addition of hardener and thinner. TEKNOCOAT TINTER is not mixable with NICOSIT 1304 and NICOLET 1230.
-------------------------------	--

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.
