

**PAINT TYPE** Hardener.**USAGE** This hardener is intended for use in the following product types:TEKNODUR 3730  
TEKNODUR 3740  
TEKNODUR 0150  
TEKNODUR 0190**SPECIAL PROPERTIES** -**DIRECTION FOR USE****Mixing ratio** The mixing ratio between the base coat and hardener is stated on the base label.

If the mixing ratio is stated in volume-% use a litre measure or a measure stick.

To achieve a satisfactory result, it is important that the hardener is mixed correctly.

15 minutes after the addition of hardener the viscosity increases. Final adjustment of the spraying viscosity has to be made after this time period.

**Storage** It is important that the container is closed tightly after use as the hardener reacts with the humidity of the air.**SAFETY MARKINGS** See Safety Data Sheet.**ADDITIONAL INFORMATION** Storage: See label.  
Store in a tightly closed container.

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com).