

<b>TYPE</b>	Hardener for water borne, two pack polyurethane topcoat.
<b>USE</b>	The hardener is for use in the following product type:  TEKNODUR AQUA 3393, TEKNODUR AQUA 3394, TEKNOCAT AQUA 1330-0X and TEKNOCOAT AQUA 1330-4X.

**TECHNICAL DATA**

<b>Mixing ratio</b>	The mixing ratio for the base coat and the hardener is stated on the base label.  The base and hardener are mixed together and stirred mechanically thoroughly before application. The hardener is mixed to the base in one single pour. The stirring time should be at least 5 minutes. Inadequate stirring results in imperfect curing and impaired film properties. The product can also be used in two pack plants. Ready paint should be used within 3 hours from the mixing procedure otherwise the mixture becomes unfit for use.
<b>Volatile organic compound (VOC)</b>	See Safety Data Sheet.

**DIRECTIONS FOR USE**

<b>Cleaning of equipment</b>	Equipment: Clean with TEKNOSOLV 6220, TEKNOSOLV 6240 or GORI 910.005.  Two pack plants – contact TEKNOS or equipment supplier: Clean the hardener with TEKNOSOLV 6220, TEKNOSOLV 6240 or GORI 910.005.  One pack plants: Clean the mixing product with TEKNOSOLV 7030 or TEKNOCLEAN 1950.
<b>Storage</b>	Before opening and application the hardener must be temperate.  It is important that the container is closed tightly after use as the hardener reacts to air humidity.  The product must be stored frost-free.
<b>HEALTH AND SAFETY</b>	See Safety Data Sheet.
<b>ADDITIONAL INFORMATION</b>	Storage: See label. Store in a tightly closed container.