SAFETY DATA SHEET



TEKNODUR AQUA 3393-05

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : TEKNODUR AQUA 3393-05

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product description : Paint.

1.3 Details of the supplier of the safety data sheet

Teknos (UK) Limited, Unit E1, Heath Farm, Banbury Road, Swerford, Oxfordshire OX7 4BN, United Kingdom. Tel. +44 (0) 1608 683 494.

Teknos Group Oy, Takkatie 3, FI-00370 HELSINKI, FINLAND. Tel. +358 9 506 091.

E-mail: msds@teknos.dk

National contact

Teknos (UK) Limited, Unit E1, Heath Farm, Banbury Road, Swerford, Oxfordshire OX7 4BN, United Kingdom. Tel. +44 (0) 1608 683 494.

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : NHS: 111 (for advise), 999 (for emergency).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition: Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Signal word

Hazard statements : H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention: P273 - Avoid release to the environment.

Response : Not applicable.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Supplemental label

elements

: Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no.

247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1), Bis(1,2,2,6, 6-pentamethyl-4-piperidyl)sebacat and Hydroxyphenylbenzotriazol derivatives. May

produce an allergic reaction.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue : 16/11/2015 Version : 1.01 1/12

SECTION 2: Hazards identification

2.3 Other hazards

Other hazards which do not result in classification

: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

Product/ingredient name	Identifiers	%	Classification Regulation (EC) No. 1272/2008 [CLP]	Туре
2-Butoxyethanol	REACH #: 01-2119475108-36 EC: 203-905-0 CAS: 111-76-2 Index: 603-014-00-0	≥1 - <3	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319	[1] [2]
Hydroxyphenylbenzotriazol derivatives	REACH #: 01-0000015075-76 CAS: 104810-48-2	≥0.3 - <1	Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
Bis(1,2,2,6,6-pentamethyl- 4-piperidyl)sebacat	REACH #: 01-2119491304-40 EC: 255-437-1 CAS: 41556-26-7	≥0.25 - <0.3	Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1]
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9 Index: 613-167-00-5	<0.0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 See Section 16 for the full text of the H statements declared above.	[1]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue : 16/11/2015 Version : 1.01 2/12

SECTION 4: First aid measures

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous combustion products

: In a fire, decomposition may produce toxic gases/fumes.

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue : 16/11/2015 Version : 1.01 3/12

SECTION 5: Firefighting measures

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand. earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

: 16/11/2015

7.2 Conditions for safe storage, including any incompatibilities

Label No: 11763 Date of issue/Date of revision Version: 1.01 4/12

: 16/11/2016 Date of previous issue

TEKNODUR AQUA 3393-05

SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

2-Butoxyethanol

EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.

STEL: 50 ppm 15 minutes. TWA: 25 ppm 8 hours.

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Hydroxyphenylbenzotriazol derivatives	DNEL	Long term Inhalation	0.35 mg/m ³	Workers	Systemic
	DNEL DNEL	Long term Dermal Long term Inhalation	0.5 mg/kg 0.085 mg/ m³	Workers Consumers	Systemic Systemic
	DNEL DNEL	Long term Dermal Long term Oral	0.25 mg/kg 0.025 mg/ kg	Consumers Consumers	Systemic Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Hydroxyphenylbenzotriazol derivatives	Fresh water Marine water Sewage Treatment Plant	0.0023 mg/l 0.00023 mg/l 10 mg/l	-
	Fresh water sediment Marine water sediment Soil	3.06 mg/kg 0.306 mg/kg 2 mg/kg	- - -

8.2 Exposure controls

Appropriate engineering controls

 Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

TEKNODUR AQUA 3393-05

Date of issue/Date of revision: 16/11/2016 **Date of previous issue**: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **5/12**

Date of issue/Date of revision: 1.01 **Date of previous issue**

Date of issue/Date of revision: 1.01 **Date of previous issue**

Date of issue/Date of revision

**Date of issue/Date o

SECTION 8: Exposure controls/personal protection

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Recommendations: Wear suitable gloves tested to EN374. > 8 hours (breakthrough time): Nitrile gloves. thickness > 0.3 mm

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

polyvinyl alcohol (PVA) gloves

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

spray application Filter type: A F

Not recommended

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state : Liquid.
Colour : Various
Odour : Slight

Odour threshold : Not available.

pH : 7.5 - 8.5

Melting point/freezing point : Not available.

Initial boiling point and : Not available.

boiling range

Flash point : Closed cup: >100°C

Evaporation rate : Not available.

Flammability (solid, gas) : Not available.

Upper/lower flammability or explosive limits : Lower: 2.2% Upper: 13%

Vapour pressure : Not available.

Vapour density : Not available.

Density : 1 kg/l

TEKNODUR AQUA 3393-05

Date of issue/Date of revision: 16/11/2016 **Date of previous issue**: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision: 16/11/2016 **Date of previous issue**

Date of issue/Date of revision: 16/11/2015 **Version**: 1.01 **6/12**

Date of issue/Date of revision

**Date of issue/

SECTION 9: Physical and chemical properties

Solubility(ies) : Not available.

Partition coefficient: n-octanol/ : Not available.

water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not available.

Explosive properties : Not available.

Oxidising properties : Not available.

9.2 Other information

VOC : 57 g/l

No additional information.

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Hydroxyphenylbenzotriazol derivatives	LC50 Inhalation Vapour	Rat	>5.8 mg/l	4 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral	Rat	53 mg/kg	-

Conclusion/Summary: Not available.

Acute toxicity estimates

Route	ATE value	
Dermal	25926.2 mg/kg 41508.8 mg/kg 415.1 mg/l	

Irritation/Corrosion

TEKNODUR AQUA 3393-05

Date of issue/Date of revision: 16/11/2016 **Date of previous issue**: 16/11/2015 **Version**: 1.01 **7/12**

**Ver

SECTION 11: Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
2-Butoxyethanol	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Skin - Severe irritant	Human	-	0.01 Percent	-

Conclusion/Summary: Not available.

Sensitisation

Product/ingredient name	Route of exposure	Species	Result
Hydroxyphenylbenzotriazol derivatives	skin	Guinea pig	Sensitising

Conclusion/Summary: Not available.

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Hydroxyphenylbenzotriazol derivatives	-	Subject: Bacteria	Negative
donvativos	-	Subject: Mammalian-Animal	Negative

Conclusion/Summary: Not available.

Carcinogenicity

Conclusion/Summary: Not available.

Reproductive toxicity

Conclusion/Summary: Not available.

Teratogenicity

Conclusion/Summary: Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on the likely : Not available.

routes of exposure

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue : 16/11/2015 Version : 1.01 8/12

SECTION 11: Toxicological information

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

Potential delayed effects

: Not available.

Long term exposure

Potential immediate

: Not available.

Potential delayed effects

: Not available.

Potential chronic health effects

Not available.

effects

effects

Conclusion/Summary : Not available.

General No known significant effects or critical hazards. Carcinogenicity : No known significant effects or critical hazards. Mutagenicity : No known significant effects or critical hazards. : No known significant effects or critical hazards. **Teratogenicity Developmental effects** : No known significant effects or critical hazards. **Fertility effects** : No known significant effects or critical hazards.

Other information : Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-Butoxyethanol	Acute EC50 >1000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 800000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 1250000 µg/l Marine water	Fish - Menidia beryllina	96 hours
Hydroxyphenylbenzotriazol derivatives	Acute EC50 4 mg/l	Daphnia	48 hours
	Acute LC50 2.8 mg/l	Fish	96 hours
Bis(1,2,2,6,6-pentamethyl- 4-piperidyl)sebacat	EC50 1.68 mg/l	Aquatic plants - Desmodesmus subspicatus	72 hours
	LC50 0.9 mg/l	Fish - Brachydanio rerio	96 hours

: Not available. **Conclusion/Summary**

12.2 Persistence and degradability

No known significant effects or critical hazards. **Conclusion/Summary** : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2-Butoxyethanol	0.81	-	low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

12.5 Results of PBT and vPvB assessment

PBT : Not applicable.

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue Version: 1.01 9/12 : 16/11/2015

SECTION 12: Ecological information

vPvB : Not applicable.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste

The classification of the product may meet the criteria for a hazardous waste.

European waste catalogue: 080112

(EWC)

Packaging

Methods of disposal

: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

TEKNODUR AQUA 3393-05 Label No: 11763

Date of issue/Date of revision Version: 1.01 10/12 : 16/11/2016 Date of previous issue : 16/11/2015

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions

on the manufacture,

placing on the market

and use of certain

dangerous substances,

mixtures and articles

Other EU regulations

Europe inventory: Not determined.

Seveso Directive

This product is not controlled under the Seveso Directive.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol (Annexes A, B, C, E)

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

15.2 Chemical Safety

Assessment

: Not applicable.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and

: ATE = Acute Toxicity Estimate

acronyms

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Aquatic Chronic 3, H412	Calculation method

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue : 16/11/2015 Version : 1.01 11/12

SECTION 16: Other information

Full text of abbreviated H	: H301	Toxic if swallowed.
statements	H302	Harmful if swallowed.
	H311	Toxic in contact with skin.
	H312	Harmful in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H319	Causes serious eye irritation.
	H331	Toxic if inhaled.
	H332	Harmful if inhaled.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.
	H412	Harmful to aquatic life with long lasting effects.

Full text of classifications [CLP/GHS]

H412	Harmful to aquatic life with long lasting effects.
 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 4, H332	ACUTE TOXICITY (oral) - Category 3 ACUTE TOXICITY (dermal) - Category 3 ACUTE TOXICITY (inhalation) - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 ACUTE AQUATIC HAZARD - Category 1
Aquatic Chronic 1, H410 Aquatic Chronic 2, H411	LONG-TERM AQUATIC HAZARD - Category 1 LONG-TERM AQUATIC HAZARD - Category 2 LONG-TERM AQUATIC HAZARD - Category 3 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
Eye Irrit. 2, H319	SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2
Skin Corr. 1B, H314 Skin Irrit. 2, H315 Skin Sens. 1, H317	SKIN CORROSION/IRRITATION - Category 1B SKIN CORROSION/IRRITATION - Category 2 SKIN SENSITIZATION - Category 1

Date of issue/ Date of

revision

: 16/11/2016

Date of previous issue : 16/11/2015

Version : 1.01

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

TEKNODUR AQUA 3393-05 Label No :11763

Date of issue/Date of revision : 16/11/2016 Date of previous issue : 16/11/2015 Version : 1.01 12/12