

TYPE	Water borne colorant.
USE	All types of wood.
SPECIAL PROPERTIES	TEKNOSTAIN AQUA 1996-10 TINTER is based on pigments.

TECHNICAL DATA

Density	Approx. 1.03-1.06 kg/l (approx.. 71 % for White).
Solid	Approx. 9-11 % by weight (approx.. 71 % for White).
Volatile organic compound (VOC)	See Safety Data Sheet.
Storage	Storage stability: See label.
System	To be used with TEKNOSTAIN AQUA 1996-00 Base T. 1T804504XXX, TEKNOSTAIN AQUA 1996-10 TINTER, BLACK 1T804201XXX, TEKNOSTAIN AQUA 1996-10 TINTER, BLUE 1T804302XXX, TEKNOSTAIN AQUA 1996-10 TINTER, GREEN 1T804406XXX, TEKNOSTAIN AQUA 1996-10 TINTER, RUBY RED 1T804405XXX, TEKNOSTAIN AQUA 1996-10 TINTER, BRIGHT RED 1T804904XXX, TEKNOSTAIN AQUA 1996-10 TINTER, YELLOW 1T804804XXX, TEKNOSTAIN AQUA 1996-10 TINTER, WHITE

INSTRUCTION FOR USE

Application method	Spraying, dipping and flow coat.				
Drying time	<table><tr><td><u>20 °C</u></td><td><u>40 °C</u></td></tr><tr><td>1 hour.</td><td>10 min.</td></tr></table>	<u>20 °C</u>	<u>40 °C</u>	1 hour.	10 min.
<u>20 °C</u>	<u>40 °C</u>				
1 hour.	10 min.				
Thinner	Water				
Cleaning	Water and TEKNOCLEAN 1954-00.				

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.