

TYPE	Water borne stain concentrate.
USE	For industrial treatment of all spruce and pine. Suitable for the colouring of pallets.
SPECIAL PROPERTIES	TEKNOSTAIN AQUA 1996-12 is based on pigment and binder.

TECHNICAL DATA

Density	Approx. 1.03-1.10 kg/l – depending on the colour.	
Solid	Approx. 20-40 % – depending on the colour.	
Volatile organic compound (VOC)	See Safety Data Sheet.	
Drying time	<u>20 °C</u> 20 min.	<u>50 °C</u> 5 min.

INSTRUCTION FOR USE

Application method	Spraying, dipping and flow coat.	
Thinner	Water	
Mixing ratio	TEKNOSTAIN AQUA 1996-12:	1 part
	Water:	20 parts
Cleaning	Water or TEKNOCLEAN 1954-00.	

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

ADDITIONAL INFORMATION

Storage	Storage stability: See label.
----------------	-------------------------------

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage www.teknos.com.