

---

<b>TYPE</b>	Water borne stain.
<b>USE</b>	For industrial treatment of all types of wood.
<b>SPECIAL PROPERTIES</b>	TEKNOSTAIN AQUA is based on soluble dyestuff, pigment and binder. Intended for indoor use.

---

**TECHNICAL DATA**

<b>Density</b>	Approx. 1.0 kg/l – depending on the colour.	
<b>Solid</b>	1-20 % – depending on the colour.	
<b>Volatile organic compound (VOC)</b>	See Safety Data Sheet.	
<b>Drying time</b>	<u>20 °C</u> 1 h	<u>40 °C</u> 10 min.

**INSTRUCTION FOR USE**

<b>Application method</b>	Spraying, dipping and floating machine.
<b>Cleaning</b>	Water and Hydren 1T021010-1.
<b>System treatment</b>	Can be overcoated with most of our clear lacquers.

<b>HEALTH AND SAFETY</b>	See Safety Data Sheet.
--------------------------	------------------------

**ADDITIONAL INFORMATION**

<b>Storage</b>	Storage stability: See label.
----------------	-------------------------------

---

The above information is normative and based on laboratory tests and practical experiences. The information is noncommittal, and we cannot accept liability for the results obtained under working conditions beyond our control, and consequently the buyer or the user is not released from the obligation to test the suitability of our products for specific means and application methods under the actual application conditions. Our liability covers only damage caused directly by defects in the products supplied by Teknos. The latest versions of Teknos' Technical Data Sheets and Safety Data Sheets are available from our homepage [www.teknos.com](http://www.teknos.com).

---