

TEKNOSTAIN AQUA CONC. 1995

Aqua Top Stain Concentrate

1995-XX

TYPE	TEKNOSTAIN AQUA Concentrate is a water borne concentrate that is to be diluted with water or water borne lacquer prior to staining
USE	For industrial staining of pine.
SPECIAL PROPERTIES	After dilution TEKNOSTAIN AQUA Concentrate possesses excellent wetting properties and provides a smooth uniform surface when staining. Used in water borne lacquer the stain concentrate provides "glow".

TECHNICAL DATA

Specific gravity	1.0 kg/l
Volatile organic compound (VOC)	See Safety Data Sheet.
Storage	To be protected against frost. Storage: See label. Store in a tightly closed container.
Application method	Stain: By staining machine, brush, spraying or dipping. Water born lacquer: Spraying.
Drying	Air, oven drying.

DIRECTIONS FOR USE

Application data	To be diluted with water prior to staining. Finishing treatment is necessary. For this purpose we recommend AC-lacquers, Water borne lacquers, UV-lacquers as well as oils. By application of water borne lacquers please note that there is a slight risk of the stain dissolving in the lacquer. This stain concentrate could be added to water borne lacquer to add some "glow". When added to water borne lacquer the drying conditions for water borne lacquer apply.
Drying	The stain is ready for overcoating or oil treatment after 30 min. air-drying. Forced drying may be used, thus reducing the drying time.
Cleaning	Tools are cleaned with water.

HEALTH AND SAFETY	See Safety Data Sheet.
--------------------------	------------------------

ADDITIONAL INFORMATION	TEKNOSTAIN AQUA should not get in touch with metal as this might cause discoloration. A trial staining should be carried out to check the colour as variations of structure and natural colour of the wood, and method of application may cause a considerable colour deviation compared to the sample approved.
-------------------------------	--