

# SAFETY DATA SHEET

Product & Reference: IN7NW Range Traff TX200 Acid Curing Enamels.

Date of Issue: 5.8.02

VERSION: Revision 2

Page 1 of 6

## 1. IDENTIFICATION OF THE PREPARATION AND COMPANY

Product code and name: IN7NW Range TX200 Acid Curing Enamels.  
See Section 16 for range of products covered by this safety data sheet.

Intended use: A fast drying acid curing enamel intended for application by spray or curtain coater to furniture and fittings for indoor use.

Name, address and telephone number: Akzo Nobel Industrial Coatings Ltd, PO Box 37, Crown House, Hollins Road, Darwen, Lancashire, United Kingdom, BB3 0BG. Telephone: +44 (0)1254 760760

Emergency telephone number: +44 (0)1254 760760

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances presenting a health or environmental hazard within the meaning of Chemicals (Hazard Information and Packaging for Supply) Regulations (CHIP) or assigned occupational exposure limits.

Substance	Concentration Range %	Symbol Letter	R-phrases (*)	EINECS/ELINCS No.	CAS No.
butyl acetate	20 - 30%	--	R66, R67	204-658-1	123-86-4
butan-1-ol	1 - 10%	Xn	R22, R37/38, R41, R67	200-751-6	71-36-3
butyl glycol acetate	1 - 5%	Xn	R20/21	203-933-3	112-07-2
methoxy propyl acetate	1 - 5%	Xi	R36	203-603-9	108-65-6
1-methoxypropan-2-ol	5 - 10%	--	--	203-539-1	107-98-2
Nitrocellulose	1 - 10%	--	--	-	9004-70-0

(\*) for full text see Section 16

## 3. HAZARDS IDENTIFICATION

Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.  
Avoid breathing spray mist and vapour during application. Flammable liquid and vapour keep away from sources of ignition.

## 4. FIRST AID MEASURES

### General:

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

### Inhalation:

Remove to fresh air, keep the patient warm and at rest. If breathing has stopped, administer artificial respiration. Give nothing by mouth. If unconscious, place in a prone position with head to the side (recovery position) and seek medical advice.

### Eye contact:

Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart, and seek medical advice.

### Skin Contact:

Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners.

### Ingestion:

If accidentally swallowed obtain immediate medical attention, preferably at the nearest hospital accident emergency unit. Show this safety data sheet. Keep at rest. Do NOT induce vomiting. If conscious give milk or water to drink.

## 5. FIRE FIGHTING MEASURES

### Extinguishing media:

Recommended: alcohol resistant foam, CO<sub>2</sub>, powder, water spray/mist.

Not to be used: water jet.

### Recommendations:

Fire will produce dense black smoke containing hazardous product of combustion (see Section 10). Decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow runoff from fire fighting to enter drains or water courses.

# SAFETY DATA SHEET

Product & Reference: IN7NW Range Traff TX200 Acid Curing Enamels.

Date of Issue: 5.8.02

VERSION: Revision 2

Page 2 of 6

## 6. ACCIDENTAL RELEASE MEASURES

Exclude sources of ignition and ventilate the area. Warn others of the dangers present and exclude non-essential personnel. Avoid breathing vapours. Floors may become slippery. Refer to protective measures listed in Sections 7 and 8. Contain and collect spillages with non-combustible absorbent materials, eg, sand, earth, vermiculite, diatomaceous earth and place in a clearly labelled suitable container for disposal in accordance with the waste regulations (see Section 13). Do not allow to enter drains or water courses.

Clean preferably with a detergent; avoid the use of solvents.

If the product enters drains or sewers the local water company should be contacted immediately; in the case of contamination of stream, rivers or lakes, the relevant environment agency.

## 7. HANDLING AND STORAGE

### Handling

Use product only in accordance with methods stated in Section 1.

Solvent vapours are heavier than air and may spread along floors. They may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

Additionally, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard. Keep the container tightly closed. Exclude sources of heat, sparks and open flame.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist.

Smoking, eating and drinking should be prohibited in areas of storage and use.

For Occupational Exposure Controls, see Section 8.

Never use pressure to empty; the container is not a pressure vessel.

Always keep in containers made of the same material as the supply container.

The accumulation of contaminated rags and dry overspray, particularly in spray booth filters, may result in spontaneous combustion.

Good housekeeping standards and regular safe removal of waste materials and regular maintenance of spray booth filters will minimise risks of spontaneous combustion and other fire hazards.

The Manual Handling Operations Regulations 1992 may apply to the handling of containers of this product. To assist employers the following method of calculating the weight for any pack size is given.

Take the pack size volume in litres and multiply this figure by the specific gravity value given in Section 9. This will give the net weight of the coating in kilograms. Allowance will then have to be made for the immediate packaging to give an approximate gross weight.

### Storage

The storage and use of this product is subject to the requirements of the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations. Up to 50 litres of such highly flammable liquids may be kept in a work room provided they are kept in a fireproof cupboard or bin. Larger quantities must be kept in a separate storeroom conforming to the structural requirements of the regulations.

Further guidance is contained in HSE guidance note HS(G)51 "Storage of Flammable Liquids in Containers" should be observed.

Observe the label precautions. Store between 5 and 25°C in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Containers which are opened should be properly resealed and kept upright to prevent leakage. The principles contained in the HSE's guidance note HS(G)71 "Storage of Packaged Dangerous Substances" should be observed when storing this product. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

All engineering control measures used to control exposure to hazardous substances must be selected, maintained, examined and tested to meet the requirements of the Control of Substances Hazardous to Health Regulations (COSHH). Similarly all personal protective equipment, including respiratory protective equipment, must be selected, issued and maintained to meet the requirements of COSHH. These requirements include the provision of any necessary information, instruction and training with regard to their use.

### Exposure Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and/or solvent vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn. (See "Occupational Exposure Controls" below).

# SAFETY DATA SHEET

Product & Reference: IN7NW Range Traff TX200 Acid Curing Enamels.

Date of Issue: 5.8.02

VERSION: Revision 2

Page 3 of 6

## Exposure Limit Values

Substance	8 hr TWA		15 min STEL		Notations
	ppm	mg m <sup>-3</sup>	ppm	mg m <sup>-3</sup>	
butyl acetate	150	724 OES	200	966 OES	--
butan-1-ol	--	--	50	154 OES	Sk
Methoxypropylacetate	50	274 OES	100	548 OES	IOELV, Sk
1-methoxypropan-2-ol	100	375 OES	150	560 OES	Sk, IOELV

### Notes:

OES	-	occupational exposure standard (EH40 table 2)
MEL	-	maximum exposure limit (EH40 table 1/COSHH Schedule 1)
SUP	-	OEL assigned by the supplier of the substance
TWA	-	time weighted average
ppm	-	parts per million
mg m <sup>-3</sup>	-	milligrams per cubic metre
Sk	-	indicates a risk of absorption through skin
Sen	-	indicates a respiratory sensitiser
STEL	-	short term exposure limit
Bmgv	-	biological monitoring may be appropriate
ILV	-	indicative limit value
IOELV	-	indicative occupational exposure limit value

## Occupational Exposure Controls

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

### Respiratory protection:

Air-fed respiratory protective equipment should be worn when this product is sprayed if the exposure of the sprayer or other people nearby cannot be controlled to below the occupational exposure limit and engineering controls and methods cannot reasonably be improved.

Dry sanding of the dry paint film will give rise to dust. Wet sanding should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be worn.

### Hand Protection:

Where skin exposure may occur wear impervious gloves, advice should be sought from glove suppliers on appropriate types and usage times for this product. The instructions and information provided by the glove supplier on use, storage, maintenance and replacement must be followed. Barrier creams may help to protect exposed areas of the skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred.

### Eye Protection:

Eye protection designed to protect against liquid splashes should be worn.

### Skin Protections:

Cotton or cotton/synthetic coveralls or coveralls are normally suitable. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. Regular skin inspection of users of this product is recommended. ALWAYS WASH YOUR HANDS BEFORE EATING, SMOKING OR USING THE TOILET.

### Environmental exposure control:

See Section 12 for detailed information.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

physical state: viscous liquid  
flash point: 26°C Abel closed cup  
specific gravity: 1.09 - 1.26 Kg/L @ 21°C  
vapour density: heavier than air  
lower explosion limit: 1% vv  
solubility in water: immiscible

method: BS3900 Part A9  
method: BS3900 Part A12

# SAFETY DATA SHEET

Product & Reference: IN7NW Range Traff TX200 Acid Curing Enamels.

Date of Issue: 5.8.02

VERSION: Revision 2

Page 4 of 6

## 10. STABILITY AND REACTIVITY

Stable under the recommended storage and handling conditions. (See section 7). In a fire, hazardous decomposition and products such as smoke, carbon monoxide, carbon dioxide and oxides of nitrogen may be produced.

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself. The product has been assessed following the conventional method in CHIP and is classified for toxicological hazards accordingly. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short term and long term exposure by oral, inhalation and dermal routes of exposure and eye contact. See sections 3 and 15 for details of the resulting hazard classification.

### Inhalation

Exposure to organic solvent vapours may result in adverse health effects such as irritation of the mucous membrane and the respiratory system and adverse effects on the renal and central nervous systems. Symptoms include coughing, headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

### Skin

Solvents may cause some of the above effects by absorption through the skin.

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in nonallergic contact dermatitis and absorption through the skin.

### Eyes

Splashes in the eyes may cause irritation and reversible local damage.

### Ingestion

Ingestion may result in the following effects: sore throat, abdominal pain, drowsiness, nausea, vomiting and diarrhoea. Other effects may be as described for exposure to vapours.

## 12. ECOLOGICAL INFORMATION

There is no data available on the product itself.

The product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters. The Air Pollution Control requirements of regulations made under the Environmental Protection Act may apply to the use of this product. The product has been assessed following the conventional method in CHIP and is not classified as dangerous for the environment.

## 13. DISPOSAL CONSIDERATIONS

Do not allow into drains or water courses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using the information provided in this safety data sheet, advice should be obtained from the relevant environment agency whether the special waste regulations apply.

## 14. TRANSPORT INFORMATION

**Transport within users premises:** Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

**Onward transport, subsequent to purchase:**

Transport to be in accordance with ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport.

Class: 3

Sub Hazard: -

Packing Group: III

Ensure drivers have adequate training.

Proper Shipping Name: Paint

UN Number: 1263

For international road/rail transport:

Class: 3

Packing Group: III

For Sea Transport:

Marine Pollutant: No

EmS: 3.05

# SAFETY DATA SHEET

Product & Reference: IN7NW Range Traff TX200 Acid Curing Enamels.

Date of Issue: 5.8.02

VERSION: Revision 2

Page 5 of 6

## 15. REGULATORY INFORMATION

The product is classified and labelled for supply in accordance with the CHIP Regulations as follows:

### FLAMMABLE

Repeated exposure may cause skin dryness or cracking

Vapours may cause drowsiness and dizziness

Do not breathe gas/fumes/vapour/spray.

In case of insufficient ventilation, wear suitable respiratory equipment.

The information contained in this safety data sheet does not constitute the user's own assessment of workplace risks as required by other health and safety legislation. The provisions of the Health and Safety at Work etc. Act and the Control of Substances Hazardous to Health Regulations apply to the use of this product at work.

## 16. OTHER INFORMATION

Text of R phrases listed in Section 2.

R No:	Phrase
R20	Harmful by inhalation
R21	Harmful in contact with skin
R22	Harmful if swallowed
R36	Irritating to eyes
R37	Irritating to respiratory system
R38	Irritating to skin
R41	Risk of serious damage to eyes
R66	Repeated exposure may cause skin dryness or cracking
R67	Vapours may cause drowsiness and dizziness

The information contained in this safety data sheet is provided in accordance with the requirements of the CHIP Regulations.

The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instruction.

As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

Further guidance on OELs and the assessment of occupational exposure to substances hazardous to health is given in "EH40 : Occupational exposure limits" published by the HSE, Books.

The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Further information and relevant advice can be found in:

The Control of Substances Hazardous to Health Regulations 1999 (SI 1999 : 437)

COSHH Essentials: easy steps to control chemicals, HS (G) 193. Details of available Control Guidance Sheets, which may be relevant to the particular conditions of use, can also be found in HS (G) 193

The Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972 (SI 1972 : 917)

The Manual Handling Operations Regulations 1992 (SI 1992 : 2793)

Chemical Warehousing: Storage of Flammable Liquids in Containers, HS(G)51

Chemical Warehousing: Storage of Packaged Dangerous Substances, HS(G)71

The Environmental Protection (Duty of Care) Regulations 1992 (SI 1992 : 2839)

Spraying of highly flammable liquids EH9 (HSE)

A Guide to Working with Solvents, INDG 272

## **SAFETY DATA SHEET**

Product & Reference: IN7NW Range Traff TX200 Acid Curing Enamels.

Date of Issue: 5.8.02

VERSION: Revision 2

Page 6 of 6

### **Range of Products Covered by this Safety Data Sheet:**

IN7NW000	TX200	Base 00
IN7NW001	TX200	Base 01
IN7NW003	TX200	Base 03
IN7NW321	TX200	Base YX21
IN7NW457	TX200	Base BX57
IN7NW534	TX200	Base RX34
IN7NW544	TX200	Base RX44
IN7NW550	TX200	Base RX50
IN7NW685	TX200	Base GX85

### **Revision 2**

Sections 1, 2, 7, 8, 11, 12, 13, 14 and 16 have been revised .



**Holman Specialist Paints Ltd.**

1 CENTRAL TRADING ESTATE, SIGNAL WAY, SWINDON SN3 1PD  
TEL: (01793) 511537 FAX: (01793) 431142