

**SAFETY DATA SHEET** 

**ULTRA LUX** 

# SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: ULTRA LUX
Product code	: 697-s
Product description	: A waterborne acrylate paint.

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

### 1.3 Details of the supplier of the safety data sheet

Manufacturer or Distributor		
Tikkurila Oyj		
P.O. Box 53 FI-01301 VANTAA		
FINLAND		
Telephone +358 20 191 2000		
e-mail address of person responsible for this SDS	:	Tikkurila Oyj, Product Safety, e-mail: productsafety@tikkurila.com

#### 1.4 Emergency telephone number

Telephone number	: 1 (2	12 24h)
Supplier or Manufacturer		
Telephone number		ïkkurila Oyj 358 20 191 2000 (GMT +2) Mon-Fri 8-16

### **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1, H317 Aquatic Chronic 2, H411

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

2.2 I	_abel	elem	ents

Hazard pictograms



Signal word Hazard statements	:Warning :H317 - May cause an allergic skin reaction.
Precautionary statements	H411 - Toxic to aquatic life with long lasting effects.
General	<ul> <li>P102 - Keep out of reach of children.</li> <li>P101 - If medical advice is needed, have product container or label at hand</li> </ul>

Date of issue/Date of revision	20.12.2016 Date of previous issue 20.12.2016. ULTRA LUX
Prevention	<ul> <li>P261 - Avoid breathing mist/spray.</li> <li>P280 - Wear protective gloves.</li> <li>P271 - Use only outdoors or in a well-ventilated area.</li> <li>P273 - Avoid release to the environment.</li> </ul>
Response	: P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
Storage	: Not applicable.
Disposal	: Not applicable.
Hazardous ingredients	<ul> <li>2-octyl-2H-isothiazol-3-one</li> <li>3-iodo-2-propynyl butylcarbamate</li> <li>4,5-dichloro-2-octyl-2H-isothiazol-3-one</li> <li>1,2-benzisothiazol-3(2H)-one</li> <li>reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and</li> <li>2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)</li> </ul>
Supplemental label elements	: Not applicable.

### **Treated articles**

This product contains a biocidal product for the preservation of the product during storage. Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).

### 2.3 Other hazards

Other hazards which do : None known. not result in classification

# **SECTION 3: Composition/information on ingredients**

3.2 Mixtures	: Mixture	1	1 1	
			<b>Classification</b>	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
2-octyl-2H-isothiazol-3-one	EC: 247-761-7 CAS: 26530-20-1 Index: 613-112-00-5	≤0,3	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	-
3-iodo-2-propynyl butylcarbamate	EC: 259-627-5 CAS: 55406-53-6	≤0,3	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (larynx) Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)	-
4,5-dichloro-2-octyl-2H-isothiazol- 3-one	EC: 264-843-8 CAS: 64359-81-5	<0,1	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1C, H314 Skin Sens. 1, H317 STOT SE 3, H335 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)	-
1,2-benzisothiazol-3(2H)-one	EC: 220-120-9 CAS: 2634-33-5	<0,05	Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411	-
reaction mass of: 5-chloro-2-methyl- 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H- isothiazol-3-one [EC no. 220-239-6] (3:1)	CAS: 55965-84-9	<0,0015	Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	-

Date of issue/Date of revision	20.12.2016 Date of previous issue	20.12.2016. ULTRA LUX	
		See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

## **SECTION 4: First aid measures**

4.4 Decembrations of fired	
4.1 Description of first	ald measures
General	<ul> <li>In all cases of doubt, or when symptoms persist, seek medical attention. Show this safety data sheet or label to the doctor if possible.</li> </ul>
Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with plenty of lukewarm water, keeping eyelids open. Continue to rinse for at least 15 minutes. Get medical attention if symptoms occur.</li> </ul>
Inhalation	: Remove to fresh air. Keep person warm and at rest.
Skin contact	<ul> <li>Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. Get medical attention if symptoms occur.</li> </ul>
Ingestion	: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a position comfortable for breathing. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. See Section 11 for more detailed information on health effects and symptoms.

### 4.3 Indication of any immediate medical attention and special treatment needed

None.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media		
Suitable extinguishing media	:	Use an extinguishing agent suitable for the surrounding fire. Recommended: Alcohol resistant foam, $CO_2$ , powders or water spray/mist.
Unsuitable extinguishing media	:	Do not use a direct water jet that could spread the fire.
5.2 Special hazards arising fr	ron	n the substance or mixture
Hazards from the substance or mixture	:	This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.
Hazardous combustion products	:	When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.
5.3 Advice for firefighters		
Special protective actions for fire-fighters	:	Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.
Special protective equipment for fire-fighters	:	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

20.12.2016 Date of previous issue 20.12.2016.

ULTRA LUX

### **SECTION 6: Accidental release measures**

6.1 Personal precautions, protective equipment and emergency procedures	:	Provide adequate ventilation. Avoid breathing vapor or mist. Avoid direct skin contact with product. See Section 8 for information on appropriate personal protective equipment.
6.2 Environmental precautions	:	Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.
6.3 Methods and materials for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with water or detergent. Avoid using solvents.
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

### SECTION 7: Handling and storage

7.1 Precautions for safe handling	: Skin contact with the product and exposure to spray mist and vapor should be avoided. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. Wash hands before breaks and immediately after handling the product. Avoid release to the environment.
7.2 Conditions for safe storage, including any incompatibilities	: Store in original container protected from direct sunlight in a dry, cool and well- ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Recommended storage temperature is +5°C+25°C. Do not allow to freeze. Store in accordance with local regulations.
7.3 Specific end use(s)	: None.

## **SECTION 8: Exposure controls/personal protection**

### 8.1 Control parameters

#### **Occupational exposure limits**

No exposure limit value known.

procedures

**Recommended monitoring** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available.

### 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapors below the OEL, suitable respiratory protection must be worn (see Personal protection). Comply with the health and safety at work laws.

### Individual protection measures

: Use safety eyewear (EN166), especially during spray-application. Eye/face protection

Date of issue/Date of revision		20.12.2016 Date of previous issue 20.12.2016. ULTRA LUX
Hand protection	:	Always wear approved protective gloves against chemicals. Gloves should be replaced regularly and if there is any sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Recommended glove material (EN374): > 8 hours (breakthrough time): nitrile rubber Not recommended: PVA gloves
Skin protection	:	Wear suitable protective clothing.
Respiratory protection	:	If ventilation during spray-application is inadequate, use respirators with combination filter AP, gas/dust filter (EN405:2001). Wear a half mask or full face respirator with gas and vapor filter A and dust filter P2 during sanding (EN140:1998, EN405:2001). During continuous and long-term work the use of motor-driven or air-fed respirators is recommended (EN12941:1998). Be sure to use an approved/ certified respirator or equivalent. Check that mask fits tightly and change filter regularly.
Environmental exposure controls	:	For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

# **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Appearance		
Physical state	:	Liquid.
Color	:	Various
Odor	:	Mild.
Odor threshold	:	Not relevant for the hazard assessment of the product.
рН	:	Not relevant for the hazard assessment of the product.
Melting point/freezing point	:	0°C (water)
Initial boiling point and	:	100°C (water)
boiling range		
Flash point	;	> 100 °C
Evaporation rate		Not relevant due the nature of the product.
Flammability (solid, gas)	:	Not applicable. Product is a liquid.
Upper/lower flammability or explosive limits	:	No flammable ingredients present.
Vapor pressure	:	3,2 kPa [room temperature] (water)
Vapor density	:	Not relevant for the hazard assessment of the product.
Density	:	1,01 g/cm <sup>3</sup>
Solubility(ies)	:	Miscible in water.
Partition coefficient: n-octanol/ water	:	Not available.
Auto-ignition temperature	:	Not relevant due the nature of the product.
Decomposition temperature	:	Not relevant for the hazard assessment of the product.
Viscosity	:	Not relevant for the hazard assessment of the product.
Explosive properties	:	No explosive ingredients present.
Oxidizing properties	:	No oxidizing ingredients present.

### 9.2 Other information

No additional information.

20.12.2016 Date of previous issue

ULTRA LUX

20.12.2016.

SECTION 10: Stability and reactivity		
10.1 Reactivity	See Section 10.5.	
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).	
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.	
10.4 Conditions to avoid	: Avoid extreme heat and freezing.	
10.5 Incompatible materials	<ul> <li>Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids strong alkalis</li> </ul>	
10.6 Hazardous decomposition products	: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.	;

### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

Long term exposure to spray mist may produce respiratory tract irritation. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2-octyl-2H-isothiazol-3-one	LD50 Dermal	Rabbit	690 mg/kg	-
	LD50 Oral	Rat	550 mg/kg	-
3-iodo-2-propynyl butylcarbamate	LD50 Oral	Rat	1470 mg/kg	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one	LD50 Oral	Rat	1636 mg/kg	-
1,2-benzisothiazol-3(2H)- one	LD50 Oral	Rat	1020 mg/kg	-
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	LD50 Oral	Rat	53 mg/kg	-

Not classified.

### Irritation/Corrosion

Not classified.

### Sensitization

May cause an allergic skin reaction.

Contains following preservatives or other biocides:

1,2-benzisothiazol-3(2H)-one

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 247-500-7] and 2-methyl-3-one [EC no. 3-one [EC no. 3-o

220-239-6] (3:1)

2-octyl-2H-isothiazol-3-one 2-methyl-2H-isothiazol-3-one

2,2-dibromo-3-nitrilopropionamide

3-iodo-2-propynyl butylcarbamate

4,5-dichloro-2-octyl-2H-isothiazol-3-one Mutagenicity Not classified. Carcinogenicity Not classified. Reproductive toxicity Not classified. Teratogenicity Not classified. Specific target organ toxicity (single exposure) Not classified. Specific target organ toxicity (repeated exposure) Not classified. Specific target organ toxicity (repeated exposure) Not classified. Aspiration hazard Not classified.

# **SECTION 12: Ecological information**

Ecological testing has not been conducted on this product. Do not allow to enter drains, water courses or soil.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Toxic to aquatic life with long lasting effects.

### **12.1 Toxicity**

Product/ingredient name	Result	Species	Exposure
2-octyl-2H-isothiazol-3-one	EC50 0,32 mg/l	Daphnia - Daphnia magna	48 hours
	LC50 0,047 mg/l	Fish - Oncorhynchus mykiss	96 hours
3-iodo-2-propynyl butylcarbamate	EC50 0,053 mg/l	Algae	72 hours
	EC50 0,16 mg/l	Daphnia	48 hours
	LC50 0,067 mg/l	Fish	96 hours
	NOEC 0,05 mg/l	Daphnia - Daphnia magna	21 days
4,5-dichloro-2-octyl-2H- isothiazol-3-one	Acute EC50 0,003 mg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,004 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,36 mg/l	Algae - Skeletonema costatum	72 hours
	Acute LC50 0,74 mg/l	Fish	96 hours
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Acute EC50 0,379 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,16 mg/l	Daphnia - Daphnia magna	48 hours
	Acute LC50 0,19 mg/l	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 0,0012 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours

Date of issue/Date of revision	20.12.2016 Date of previous issue	20.12.2016.	ULTRA LUX	
	Chronic NOEC 0,004 mg/l	Daphnia - D	Daphnia magna	21 days

# 12.2 Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	-	-	Readily

# 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	Bioconcentration factor [BCF]	Potential
2-octyl-2H-isothiazol-3-one	2,45	-	low

### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.

### 12.5 Results of PBT and vPvB assessment

PBT	:	Not applicable.
vPvB	:	Not applicable.

12.6 Other adverse effects : Not available.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product	
Methods of disposal	: Remove as much product as possible from the tools before cleaning. Liquid residue and cleaning liquids are hazardous waste and must not be emptied into drains or sewage system, but handled in accordance with national regulations. Product residues should be left at special companies which have permission for gathering this kind of wastes.

### European waste catalogue (EWC)

Waste code	Waste designation
08 01 11* waste paint and varnish containing organic solvents or other hazardous substances	
If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.	

### Packaging

Methods of disposal	:	Empty packaging should be disposed of in accordance with national regulations.
Special precautions	1	No additional information.

# **SECTION 14: Transport information**

20.12.2016 Date of previous issue

ULTRA LUX

20.12.2016.

	ADR/RID	IMDG	ΙΑΤΑ	
14.1 UN number	UN3082	UN3082	₩N3082	
14.2 UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-octyl-2H-isothiazol- 3-one)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-octyl-2H-isothiazol- 3-one)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2-octyl-2H-isothiazol- 3-one)	
14.3 Transport hazard class(es)	9	9	9	
14.4 Packing group		111	111	
14.5 Environmental hazards	Yes.	Yes.	Yes.	
Additional information	This product is not regulated as a dangerous good when transported in sizes of $\leq 5 \ L \ or \leq 5 \ kg$ , provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4. 1.1.4 to 4.1.1.8. Tunnel code (E)	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4. 1.1.4 to 4.1.1.8. Emergency schedules (EmS) F-A,S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8. Passenger and Cargo Aircraft Quantity limitation: 450 L Packaging instructions: 964 Cargo Aircraft Only Quantity limitation: 450 L Packaging instructions: 964 Limited Quantities - Passenger Aircraft Quantity limitation: 30 kg Packaging instructions: Y964 Special provisions	

user

**14.6 Special precautions for** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk : Not available. according to Annex II of MARPOL and the IBC Code

20.12.2016 Date of previous issue

ULTRA LUX

20.12.2016.

# **SECTION 15: Regulatory information**

		on specific for the substance or mixture				
EU Regulation (EC) No. 19 Other EU regulations	07/2006 (REACH)					
Europe inventory	: Not determined.					
15.2 Chemical Safety	: This product contains substances for which Chemical Safety Assessments are still					
Assessment	required.					
SECTION 16: Other	information					
Indicates information that	has changed from previously issu	ued version.				
Abbreviations and	, ,					
acronyms	CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]					
	DMEL = Derived Minimal Ef					
	DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement					
	PBT = Persistent, Bioaccum					
	PNEC = Predicted No Effect Concentration					
	RRN = REACH Registration vPvB = Very Persistent and					
Procedure used to derive th	•	Regulation (EC) No. 1272/2008 [CLP/GHS]				
	fication	Justification				
Skin Sens. 1, H317		Calculation method				
Aquatic Chronic 2, H411	C	Calculation method				
Full text of abbreviated H	: H301 Toxic if swallowed.					
statements	H302 Harmful if swallow					
	H311 Toxic in contact with skin. H312 Harmful in contact with skin.					
	H314 Causes severe skin burns and eye damage.					
	H315 Causes skin irritation.					
	<ul><li>H317 May cause an allergic skin reaction.</li><li>H318 Causes serious eye damage.</li></ul>					
	H330 Fatal if inhaled.					
	H331 Toxic if inhaled. H335 May cause respiratory irritation.					
		o organs through prolonged or repeated exposure.				
	H400 Very toxic to aquat					
		tic life with long lasting effects. e with long lasting effects.				
Full text of classifications		CUTE TOXICITY (inhalation) - Category 2				
[CLP/GHS]		CUTE TOXICITY (oral) - Category 3				
		CUTE TOXICITY (dermal) - Category 3				
	•	CUTE TOXICITY (inhalation) - Category 3 CUTE TOXICITY (oral) - Category 4				
	•	CUTE TOXICITY (dermal) - Category 4				
		QUATIC HAZARD (ACUTE) - Category 1				
		QUATIC HAZARD (LONG-TERM) - Category 1 QUATIC HAZARD (LONG-TERM) - Category 2				
		ERIOUS EYE DAMAGE/ EYE IRRITATION - Category				
		KIN CORROSION/IRRITATION - Category 1B				
		KIN CORROSION/IRRITATION - Category 1C KIN CORROSION/IRRITATION - Category 2				
		SKIN SENSITIZATION - Category 1				
		PECIFIC TARGET ORGAN TOXICITY (REPEATED				
	STOT SE 3, H335 S	EXPOSURE) - Category 1 PECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3				
	: 20-12-2016					
Date of issue/ Date of	-20 - 12 - 2010					

Date of issue/Date of revision	20.12.2016 Date of previous issue	20.12.2016.	ULTRA LUX	
Date of previous issue	: 20-12-2016			
Version	: 1.03			
Notice to reader				

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.