Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Regulation (EU) No. 453/2010 -

**Europe** 

Date of issue/ Date of : 10-11-2015 Date of previous issue : 10-11-2015



# SAFETY DATA SHEET

VALTTI POHJUSTE

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : VALTTI POHJUSTE

Product code : 0050900

**Product description**: Wood preservative. Retards moisture absorption as well as the spread of blue stain.

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use: Painting work

Ready-to-use solventborne colourless wood preservative that penetrates into the substrate for outdoor use (use class 2 and 3) for consumer and professional use.

The product may be used only as wood preservative according to descriptions of technical data sheet and sales package.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer or Distributor** 

Tikkurila Oyj P.O. Box 53 FI-01301 VANTAA

FINLAND

Telephone +358 20 191 2000

e-mail address of person : Tikkurila Oyj, responsible for this SDS : Product Safety,

e-mail: productsafety@tikkurila.com

#### 1.4 Emergency telephone number

Telephone number : 112

(24h)

**Supplier or Manufacturer** 

Telephone number : Tikkurila Oyj

+358 20 191 2000 Mon-Fri 8-16

## **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Asp. Tox. 1, H304 Aquatic Chronic 3, H412

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

#### 2.2 Label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H304 - May be fatal if swallowed and enters airways.

H412 - Harmful to aquatic life with long lasting effects.

Version : 1.02 1/9

**Precautionary statements** 

General: P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

**Prevention**: P261 - Avoid breathing vapor.

P271 - Use only outdoors or in a well-ventilated area.

P284 - In case of inadequate ventilation wear respiratory protection: Wear

respiratory protection.

P273 - Avoid release to the environment.

Response : P301 - IF SWALLOWED:

P310 - Immediately call a POISON CENTER or physician.

P331 - Do NOT induce vomiting.

Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents according to the local regulations for hazardous waste

and recycle or dispose container in accordance with local regulations.

Hazardous ingredients : hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Supplemental label

Deported o

elements

: Contains 3-iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking.

Wear protective gloves.

**Biocidal products regulation** 

**Active substances** 

Name %

3-iodo-2-propynyl butylcarbamate 0.7

#### 2.3 Other hazards

Other hazards which do not result in classification

: **Note!** Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials can create fire some hours later and should be soked in water and placed in a closed metal container before disposal.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures : Mixture

			<u>Classification</u>	
Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Notes
hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	REACH #: 01-2119457273-39 EC: 918-481-9	≥75 - <90	Asp. Tox. 1, H304 EUH066	-
3-iodo-2-propynyl butylcarbamate	EC: 259-627-5 CAS: 55406-53-6	≥0,3 - <1	Acute Tox. 4, H302 Acute Tox. 3, H331 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT RE 1, H372 (throat) Aquatic Acute 1, H400 Aquatic Chronic 1, H410	-
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Notes, if applicable, refer to Notes given in Annex VI of 1272/2008/EC.

Version : 1.02 2/9

### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

General : In all cases of doubt, or when symptoms persist, seek medical attention. Show this

safety data sheet or label to the doctor if possible.

**Eye contact**: Check for and remove any contact lenses. Immediately flush eyes with plenty of

lukewarm water, keeping eyelids open. Continue to rinse for at least 10 minutes.

**Inhalation** : Remove to fresh air.

Skin contact : Wash skin thoroughly with soap and water or use recognized skin cleanser. Do

NOT use solvents or thinners.

**Ingestion**: Aspiration hazard if swallowed. Can enter lungs and cause damage. If accidentally

swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Remove to fresh air and keep at rest in a

position comfortable for breathing. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters airways.

See Section 11 for more detailed information on health effects and symptoms.

Contains:

3-iodo-2-propynyl butylcarbamate May produce an allergic reaction.

#### 4.3 Indication of any immediate medical attention and special treatment needed

None.

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire. Recommended:

Alcohol resistant foam, CO<sub>2</sub>, powders or water spray/mist.

Unsuitable extinguishing

media

: Do not use a direct water jet that could spread the fire.

#### 5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: This product is not classified as flammable. Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

Hazardous thermal decomposition products

: When exposed to high temperatures, may produce hazardous decomposition products, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

#### 5.3 Advice for firefighters

Special protective actions for fire-fighters

: Use water spray to keep fire-exposed containers cool. This material is hazardous to aquatic organisms. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Special protective equipment for fire-fighters

: Appropriate breathing apparatus may be required.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: Refer to protective measures listed in sections 7 and 8.

**6.2 Environmental precautions** 

: Hazardous to aquatic environment. Do not allow to enter drains, water courses or soil.

Version : 1.02 3/9

#### 6.3 Methods and materials for containment and cleaning up

: Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Preferably clean with a detergent. Avoid using solvents.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 13 for additional waste treatment information.

# SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

: Avoid contact with skin and eyes. Avoid breathing vapor. Avoid inhalation of dust from sanding. See Section 8 for information on appropriate personal protective equipment. Eating, drinking and smoking should be prohibited in areas where this material is handled and stored. In case of skin contact, wash skin with water and soap before eating and after work. Avoid release to the environment.

If you use the product outdoors, protect soil eg with plastic. Protect other surfaces and plants from splashes. To protect the organisms that live in water, the product and the treated wood is not to be used in the immediate vicinity of the water environment (rivers, lakes, etc.)

Risk of self-ignition! Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be placed in a metal container filled with water and sealed or dried preferably outdoors or incinerated immediately. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

#### 7.2 Conditions for safe storage, including any incompatibilities

: Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from food, drink and animal feeding stuffs. No smoking. Keep only in the original container. Keep container tightly closed. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep out of the reach of children. Recommended storage temperature is +5°C ...+25°C. Store in accordance with local regulations.

#### 7.3 Specific end use(s) : None.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

procedures

**Recommended monitoring**: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available.

#### 8.2 Exposure controls

**Appropriate engineering controls** 

Provide adequate ventilation. Comply with the health and safety at work laws.

#### Individual protection measures

Eye/face protection : Safety eyewear should be used when there is a likelihood of exposure.

Version : 1.02

Hand protection : Wear protective gloves. Gloves should be replaced regularly and if there is any

sign of damage to the glove material. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be

followed.

Recommended glove material (EN374):

> 8 hours (breakthrough time): nitrile rubber, laminated foil

**Skin protection**: Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection : If ventilation is inadequate, use respirator that will protect against organic vapor and

dust/mist. Be sure to use an approved/certified respirator or equivalent. Check

that mask fits tightly and change filter regularly.

**Environmental exposure** 

controls

: For information regarding environmental protection measures, please refer to section 13 for waste handling, section 7 for handling and storage and section 1.2 for relevant identified uses of the substance or mixture and uses advised against.

# **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state : Liquid.
Color : Clear.
Odor : Strong.

Odor threshold : Not relevant for the hazard assessment of the product.

PH : Not relevant for the hazard assessment of the product.

Melting point/freezing point : <-60°C (Naphtha (petroleum), hydrotreated heavy)

Initial boiling point and

boiling range

: 155 to 217°C (Naphtha (petroleum), hydrotreated heavy)

Flash point : Closed cup: 67°C

**Evaporation rate**: Not relevant due the nature of the product.

Flammability (solid, gas) : Not applicable. Product is a liquid.

Upper/lower flammability or

explosive limits

: Lower: 1,4% (Naphtha (petroleum), hydrotreated heavy)
Upper: 7,6% (Naphtha (petroleum), hydrotreated heavy)

Vapor pressure : 0,1 to 0,3 kPa [room temperature] (Naphtha (petroleum), hydrotreated heavy)

Vapor density : Not relevant for the hazard assessment of the product.

Density : 0,8 g/cm<sup>3</sup>

Solubility(ies) : insoluble in water.

Partition coefficient: n-octanol/ : Not available.

water

**Auto-ignition temperature** : 280 to 470°C (Naphtha (petroleum), hydrotreated heavy) **Decomposition temperature** : Not relevant for the hazard assessment of the product.

Viscosity : Kinematic (40°C): <20,5 mm²/s

Explosive properties : No explosive ingredients present.

Oxidizing properties : No oxidizing ingredients present.

#### 9.2 Other information

No additional information.

# **SECTION 10: Stability and reactivity**

**10.1 Reactivity** : See Section 10.5.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : Avoid extreme heat and freezing.

Version : 1.02 5/9

#### 10.5 Incompatible materials

 Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents strong acids

10.6 Hazardous decomposition products

: When exposed to high temperatures, hazardous decomposition products may be produced, such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

# **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

There is no testdata available on the product itself.

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

strong alkalis

Exposure to component solvent vapor concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting.

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
3-iodo-2-propynyl butylcarbamate	LD50 Oral	Rat	1470 mg/kg	-

Not classified.

Irritation/Corrosion

Not classified.

Sensitization

The product is not classified as sensitizing by skin contact, but it contains following preservatives or other biocides which may produce an allergic reaction:

3-iodo-2-propynyl butylcarbamate

Mutagenicity

Not classified.

Carcinogenicity

Not classified.

Reproductive toxicity

Not classified.

**Teratogenicity** 

Not classified.

Specific target organ toxicity (single exposure)

Not classified.

Specific target organ toxicity (repeated exposure)

Not classified.

**Aspiration hazard** 

May be fatal if swallowed and enters airways.

# **SECTION 12: Ecological information**

Ecological testing has not been conducted on this product.

Do not allow to enter drains, water courses or soil.

The product is classified as environmetally hazardous according to Regulation (EC) 1272/2008. Harmful to aquatic life with long lasting effects.

#### 12.1 Toxicity

**Version** : 1.02

Product/ingredient name	Result	Species	Exposure
3-iodo-2-propynyl butylcarbamate	EC50 0,053 mg/l	Algae	72 hours
	EC50 0,16 mg/l	Daphnia	48 hours
	LC50 0,067 mg/l	Fish	96 hours
	NOEC 0,0046 mg/l	Algae - Scenedesmus subspicatus	72 hours
	NOEC 0,05 mg/l	Daphnia - Daphnia magna	21 days
	NOEC 0,0084 mg/l	Fish - Pimephales promelas	35 days

10.11.2015.

VALTTI POHJUSTE

10.11.2015 Date of previous issue

12.2 Persistence and

Date of issue/Date of revision

degradability

: No specific data.

12.3 Bioaccumulative

potential

: No specific data.

12.4 Mobility in soil

Soil/water partition

coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

PBT : Not applicable. vPvB : Not applicable.

**12.6 Other adverse effects** : Not available.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### **Product**

Methods of disposal

: Remove as much product as possible from the tools before cleaning. Avoid spillage into drains, water systems and soil. Gather residues into waste containers. Any product remaining unused and dried paint waste must be disposed of as hazardous waste in accordance with local regulations.

#### European waste catalogue (EWC)

Waste code	Waste designation
03 02 05*	other wood preservatives containing dangerous substances

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information, contact your local waste authority.

#### **Packaging**

**Methods of disposal** : Empty packaging should be recycled or disposed of in accordance with national regulations.

Special precautions

: **Risk of self-ignition!** Materials such as cleaning rags and paper wipes, sanding dust and overspray containing the product, may spontaneously self-ignite some hours later. To avoid the risks of fires, waste like this should be placed in a metal container filled with water and sealed before disposal, or dried preferably outdoors or incinerated immediately.

Version : 1.02 7/9

# SECTION 14: Transport information

This product is not regulated for carriage according to ADR/RID, IMDG, IATA.

	ADR/RID	IMDG	IATA
14.1 UN number	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-
14.3 Transport hazard class(es)	-	-	-
14.4 Packing group	-	-	-
14.5 Environmental hazards	No.	No.	No.
Additional information	-	-	-

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not available.

# SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Other EU regulations

**Europe inventory** : Not determined.

**Biocidal products** 

regulation

: This product is a biocidal product as defined in EU Regulation 528/2012.

**Authorization number** : VK-2014-0831

> Please contact the supplier to learn about other countries where this product has been registered as wood preservative. See section 1 for contact information.

This product contains substances for which Chemical Safety Assessments are still

15.2 Chemical Safety **Assessment** 

required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

vPvB = Very Persistent and Very Bioaccumulative

Version : 1.02 8/9

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification Justification

Asp. Tox. 1, H304 Expert judgment Aquatic Chronic 3, H412 Expert judgment

Full text of abbreviated H

statements

: H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

(throat) (throat)

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

Full text of classifications

[CLP/GHS]

Acute Tox. 3, H331
 Acute Tox. 4, H302
 Aquatic Acute 1, H400
 Aquatic Chronic 1, H410
 AQUATIC HAZARD (LONG-TERM) - Category 1
 Aquatic Chronic 3, H412
 AQUATIC HAZARD (LONG-TERM) - Category 3

Asp. Tox. 1, H304 ASPIRATION HAZARD - Category 1

EUH066 Repeated exposure may cause skin dryness or cracking. Eye Dam. 1, H318 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1

Skin Sens. 1, H317 SKIN SENSITIZATION - Category 1

STOT RE 1, H372 SPECIFIC TARGET ORGAN TOXICITY (REPEATED

(throat) EXPOSURE) (throat) - Category 1

Date of issue/ Date of

revision

: 10-11-2015

Date of previous issue : 10-11-2015

Version : 1.02

#### Notice to reader

This Safety Data Sheet is prepared in accordance with Annex II (EU) No 453/2010 to Regulation (EC) No 1907/2006 (REACH). The information contained in this Safety Data Sheet is based on the present state of knowledge and current EU and national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Version : 1.02 9/9